



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 16

Sista F 130 Premium

SDS No. : 485485
V003.0

Revision: 21.01.2021
printing date: 27.04.2021

Replaces version from: 04.12.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Sista F 130 Premium

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Joint sealant, acrylate

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

Fax-no.: +49 211 798 2009

ua-productsafety.de@henkel.com

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

Further information is available at Poison Control Centers.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

2.2. Label elements

Label elements (CLP):

|| The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Supplemental information EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.
Contains: 1,2-Benzisothiazol-3(2H)-one; Isothiazolinone mixture 3:1 (CIT/MIT) May produce an allergic reaction.

Precautionary statement: P102 Keep out of reach of children.
P101 If medical advice is needed, have product container or label at hand.
P262 Do not get in eyes, on skin, or on clothing.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Joint sealant, solvent-free

Base substances of preparation:

Acrylate copolymer dispersion

Inorganic fillers

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Titanium dioxide 13463-67-7	236-675-5 01-2119489379-17	1- < 5 %	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	220-120-9 01-2120761540-60	0,005- < 0,05 % (50 ppm- < 500 ppm)	Aquatic Acute 1 H400 Aquatic Chronic 2 H411 Acute Tox. 4; Oral H302 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Dam. 1 H318 Acute Tox. 2; Inhalation H330
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	01-2120764691-48	0,0001- < 0,0015 % (1 ppm- < 15 ppm)	Acute Tox. 2; Inhalation H330 Aquatic Chronic 1 H410 Acute Tox. 3; Oral H301 Acute Tox. 2; Dermal H310 Eye Dam. 1 H318 Skin Sens. 1A H317 Aquatic Acute 1 H400 Skin Corr. 1C H314 M factor (Acute Aquat Tox): 100 M factor (Chron Aquat Tox): 100

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures**4.1. Description of first aid measures**

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contact:

Rinse immediately with plenty of running water, seek medical advice if necessary.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO₂) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

Avoid contact with skin and eyes.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

Remove mechanically.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid skin and eye contact.

Hygiene measures:

- Do not eat, drink or smoke while working.
- Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

- Keep container tightly sealed.
- Store in a cool, dry place.
- Temperatures between + 5 °C and + 25 °C
- Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Joint sealant, acrylate

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Titanium dioxide 13463-67-7		1,25	Exposure limit(s):		TRGS 900
Titanium dioxide 13463-67-7			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Titanium dioxide 13463-67-7		10	Exposure limit(s):	2	TRGS 900

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Titanium dioxide 13463-67-7	aqua (freshwater)						no hazard identified
Titanium dioxide 13463-67-7	aqua (marine water)						no hazard identified
Titanium dioxide 13463-67-7	sewage treatment plant (STP)						no hazard identified
Titanium dioxide 13463-67-7	sediment (freshwater)						no hazard identified
Titanium dioxide 13463-67-7	sediment (marine water)						no hazard identified
Titanium dioxide 13463-67-7	Soil						no hazard identified
Titanium dioxide 13463-67-7	Aquatic (intermit. releases)						no hazard identified
Titanium dioxide 13463-67-7	Predator						no hazard identified
1,2-Benzisothiazol-3(2H)-one 2634-33-5	aqua (freshwater)		0,00403 mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	aqua (marine water)		0,000403 mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	aqua (intermittent releases)		0,0011 mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	sewage treatment plant (STP)		1,03 mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	sediment (freshwater)				0,0499 mg/kg		
1,2-Benzisothiazol-3(2H)-one 2634-33-5	sediment (marine water)				0,00499 mg/kg		
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Soil				3 mg/kg		
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	aqua (freshwater)		0,00339 mg/l				
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	aqua (marine water)		0,00339 mg/l				
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	sewage treatment plant (STP)		0,23 mg/l				
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	sediment (freshwater)				0,027 mg/kg		
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	sediment (marine water)				0,027 mg/kg		
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	Soil				0,01 mg/kg		
Mixture, 3(2H)-Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl-3(2H)- isothiazolone 55965-84-9	aqua (intermittent releases)		0,00339 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Workers	inhalation	Long term exposure - systemic effects		6,81 mg/m ³	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Workers	dermal	Long term exposure - systemic effects		0,966 mg/kg	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	General population	inhalation	Long term exposure - systemic effects		1,2 mg/m ³	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	General population	dermal	Long term exposure - systemic effects		0,345 mg/kg	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone 55965-84-9	Workers	inhalation	Long term exposure - local effects		0,02 mg/m ³	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone 55965-84-9	Workers	inhalation	Acute/short term exposure - local effects		0,04 mg/m ³	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone 55965-84-9	General population	inhalation	Long term exposure - local effects		0,02 mg/m ³	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone 55965-84-9	General population	inhalation	Acute/short term exposure - local effects		0,04 mg/m ³	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone 55965-84-9	General population	oral	Long term exposure - systemic effects		0,09 mg/kg	
Mixture, 3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone 55965-84-9	General population	oral	Acute/short term exposure - systemic effects		0,11 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

Ensure adequate ventilation.

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s).Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

Eye protection:

Goggles which can be tightly sealed.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance

paste

pasty

white

Odor

characteristic

Odour threshold

No data available / Not applicable

pH

Not applicable

pH	Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	No flash point up to 100°C. Aqueous preparation.
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Relative vapour density:	No data available / Not applicable
Density (20 °C (68 °F))	1,6 g/cm ³
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (23 °C (73.4 °F); Solvent: Water)	Insoluble
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable
max. VOC content:

5,2 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Titanium dioxide 13463-67-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	LD50	490 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LD50	66 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Titanium dioxide 13463-67-7	LD50	>= 10.000 mg/kg	hamster	not specified
1,2-Benzisothiazol-3(2H)-one 2634-33-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LD50	87,12 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Titanium dioxide 13463-67-7	LC50	> 6,82 mg/l	dust	4 h	rat	not specified
1,2-Benzisothiazol-3(2H)-one 2634-33-5	LC50	0,4 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LC50	0,171 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Titanium dioxide 13463-67-7	not irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	moderately irritating	4 h	rabbit	EPA OPP 81-5 (Acute Dermal Irritation)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Titanium dioxide 13463-67-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	corrosive	3 h	rabbit	EPA OPP 81-4 (Acute Eye Irritation)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	Category 1 (irreversible effects on the eye)		rabbit	not specified

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Titanium dioxide 13463-67-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	sensitising	Mouse local lymphnode assay (LLNA)	mouse	not specified

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Titanium dioxide 13463-67-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide 13463-67-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide 13463-67-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	positive without metabolic activation	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	ambiguous	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	positive	in vitro mammalian chromosome aberration test	with and without		EPA OPP 84-2 (Mutagenicity Testing)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	positive	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	not applicable		OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
Titanium dioxide 13463-67-7	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	negative	oral: unspecified		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		mouse	OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: feed		Drosophila melanogaster	OECD Guideline 477 (Genetic Toxicology: Sex-linked Recessive Lethal Test in Drosophila melanogaster)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		rat	EPA OPP 84-2 (Mutagenicity Testing)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Titanium dioxide 13463-67-7	not carcinogenic	inhalation	24 m 6 h/d; 5 d/w	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	not carcinogenic	oral: drinking water	2 y daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Titanium dioxide 13463-67-7	NOAEL P > 1.000 mg/kg NOAEL F1 > 1.000 mg/kg		oral: gavage	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	NOAEL P 112 mg/kg NOAEL F1 56,6 mg/kg NOAEL F2 56,6 mg/kg	Two generation study	oral: feed	rat	EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL P 30 ppm NOAEL F1 300 ppm NOAEL F2 300 ppm	Two generation study	oral: drinking water	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Titanium dioxide 13463-67-7	NOAEL 1.000 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	NOAEL 150 mg/kg	oral: gavage	28 days daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	NOAEL 69 mg/kg	oral: feed	90 days daily	rat	EPA OPP 82-1 (90-Day Oral Toxicity)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL 16,3 mg/kg	oral: drinking water	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL 0.34 mg/m3	inhalation: aerosol	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL 2,625 mg/kg	dermal	90 d 6 h/d	rat	EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)

Aspiration hazard:

No data available.

SECTION 12: Ecological information**General ecological information:**

Do not empty into drains, soil or bodies of water.

12.1. Toxicity**Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide 13463-67-7	LC50	Toxicity > Water solubility	48 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	LC50	2,15 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOEC	0,21 mg/l	30 d	Oncorhynchus mykiss	OECD Guideline 215 (Fish, Juvenile Growth Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LC50	0,22 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOEC	0,098 mg/l	28 d	Oncorhynchus mykiss	OECD Guideline 210 (fish early lite stage toxicity test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50	2,9 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	EC50	0,12 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOEC	1,2 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOEC	0,0036 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50	0,11 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOEC	0,0403 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	EC50	0,0052 mg/l	48 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOEC	0,00064 mg/l	48 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide 13463-67-7	EC0	Toxicity > Water solubility	24 h	Pseudomonas fluorescens	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50	23 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	EC20	0,97 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Rapidly biodegradable	aerobic	80 %	21 d	OECD Guideline 303 A (Simulation Test Aerobic Sewage Treatment. A: Activated Sludge Units)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	inherently biodegradable	aerobic	100 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	readily biodegradable	aerobic	> 60 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	6,62	56 d		not specified	other guideline:
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	3,6			calculation	QSAR (Quantitative Structure Activity Relationship)

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	0,7	20 °C	EU Method A.8 (Partition Coefficient)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	-0,71 - 0,75	20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Titanium dioxide 13463-67-7	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

080410

SECTION 14: Transport information

14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation 1005/2009/EC):	Not applicable
Prior Informed Consent (PIC) (Regulation 649/2012/EC):	Not applicable
Persistent Organic Pollutants (POPs) (Regulation 2019/1021/EC) :	Not applicable

EU. REACH, Annex XVII, Marketing and Use Restrictions (Regulation 1907/2006/EC): Not applicable

VOC Paints and Varnishes (EU):

Regulatory Basis:	Directive 2004/42/EC
max. VOC content:	5,2 g/l

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK:	WGK 1: slightly hazardous to water (Ordinance on facilities for handling substances that are hazardous to water (AwSV)) Classification according to AwSV, Annex 1 (5.2)
Storage class according to TRGS 510:	11

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.

