

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Pflege- und Korrosionsschutzöl 5 L**  
**Art.: 20760**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Care product  
Corrosion protection

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH  
Jerg-Wieland-Str. 4  
89081 Ulm-Lehr  
Tel.: (+49) 0731-1420-0  
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.

#### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.07.2020 / 0004  
 Replacing version dated / version: 22.03.2018 / 0003  
 Valid from: 17.07.2020  
 PDF print date: 22.07.2020  
 Pflege- und Korrosionsschutzöl 5 L  
 Art.: 20760



## Warning

H319-Causes serious eye irritation.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P280-Wear eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313-If eye irritation persists: Get medical advice / attention.

EUH208-Contains Di-iso-octyl amino methyl tolutriazole, 2,5-bis(octyldithio)-1,3,4-thiadiazole, Mixture of benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts, Benzene, mono-C10-14-alkyl derivs., fractionation bottoms, intermediate cut, sulfonated, sodium salts. May produce an allergic reaction.

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

<b>Distillates (petroleum), hydrotreated light naphthenic</b>	
<b>Registration number (REACH)</b>	01-2119480375-34-XXXX
<b>Index</b>	649-466-00-2
<b>EINECS, ELINCS, NLP</b>	265-156-6
<b>CAS</b>	64742-53-6
<b>content %</b>	10-30
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Asp. Tox. 1, H304
<b>Mixture of benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts</b>	<b>Substance with specific conc. limit(s) acc. to REACH-registration</b>
<b>Registration number (REACH)</b>	01-2119978241-36-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	939-603-7 (REACH-IT List-No.)
<b>CAS</b>	---
<b>content %</b>	1-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Skin Sens. 1B, H317
<b>Isotridecanol, ethoxylated</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	---
<b>CAS</b>	69011-36-5
<b>content %</b>	1-2,5

Page 3 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.07.2020 / 0004  
 Replacing version dated / version: 22.03.2018 / 0003  
 Valid from: 17.07.2020  
 PDF print date: 22.07.2020  
 Pflege- und Korrosionsschutzöl 5 L  
 Art.: 20760

<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Acute Tox. 4, H302 Eye Dam. 1, H318
<b>Benzene, mono-C10-14-alkyl derivs., fractionation bottoms, intermediate cut, sulfonated, sodium salts</b>	
<b>Registration number (REACH)</b>	01-2119985162-35-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	285-597-8
<b>CAS</b>	85117-47-1
<b>content %</b>	0,1-<1
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Skin Sens. 1B, H317
<b>2,5-bis(octyldithio)-1,3,4-thiadiazole</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	236-912-2
<b>CAS</b>	13539-13-4
<b>content %</b>	0,1-<1
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319
<b>Di-iso-octyl amino methyl toluotriazole</b>	
<b>Registration number (REACH)</b>	01-2119982395-25-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	939-700-4 (REACH-IT List-No.)
<b>CAS</b>	---
<b>content %</b>	0,1-<1
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.  
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
 Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
 Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.  
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.  
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.  
 In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### 4.3 Indication of any immediate medical attention and special treatment needed

Page 4 of 16  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 17.07.2020 / 0004  
Replacing version dated / version: 22.03.2018 / 0003  
Valid from: 17.07.2020  
PDF print date: 22.07.2020  
Pflege- und Korrosionsschutzöl 5 L  
Art.: 20760

Symptomatic treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

GB

Page 5 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.07.2020 / 0004  
 Replacing version dated / version: 22.03.2018 / 0003  
 Valid from: 17.07.2020  
 PDF print date: 22.07.2020  
 Pflege- und Korrosionsschutzöl 5 L  
 Art.: 20760

Store at room temperature.  
 Store in a dry place.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m <sup>3</sup> (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---
Monitoring procedures: - Draeger - Oil Mist 1/a (67 33 031)		
BMGV: ---	Other information: ---	

Distillates (petroleum), hydrotreated light naphthenic						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,6	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,7	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	5,4	mg/m <sup>3</sup>	

Mixture of benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - sediment, freshwater		PNEC	45211	mg/kg	
	Environment - sediment, marine		PNEC	45211	mg/kg	
	Environment - water, sporadic (intermittent) release		PNEC	1	mg/l	
	Environment - sewage treatment plant		PNEC	1000	mg/l	
	Environment - soil		PNEC	36739,74	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	8,7	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	12,5	mg/kg body weight/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	2,5	mg/kg body weight/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	35,26	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	25	mg/kg body weight/day	

Page 6 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.07.2020 / 0004  
 Replacing version dated / version: 22.03.2018 / 0003  
 Valid from: 17.07.2020  
 PDF print date: 22.07.2020  
 Pflege- und Korrosionsschutzöl 5 L  
 Art.: 20760

Workers / employees	Human - dermal	Short term, local effects	DNEL	1,04	mg/cm <sup>2</sup>	
---------------------	----------------	---------------------------	------	------	--------------------	--

<b>Benzene, mono-C10-14-alkyl derivs., fractionation bottoms, intermediate cut, sulfonated, sodium salts</b>						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	1	mg/m <sup>3</sup>	
	Environment - sediment, freshwater		PNEC	7235000 00	mg/kg dw	
	Environment - sediment, marine		PNEC	7235000 00	mg/kg dw	
	Environment - soil		PNEC	8687000 00	mg/kg dw	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	10	mg/l	
	Environment - oral (animal feed)		PNEC	16,667	mg/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,833	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1,667	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,33	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	3,33	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,66	mg/m <sup>3</sup>	

<b>Di-iso-octyl amino methyl tolutriazole</b>						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,00097 6	mg/l	
	Environment - marine		PNEC	0,00009 8	mg/l	
	Environment - sporadic (intermittent) release		PNEC	0,00976	mg/l	
	Environment - sewage treatment plant		PNEC	0,69	mg/l	
	Environment - sediment, freshwater		PNEC	0,0121	mg/kg	
	Environment - sediment, marine		PNEC	0,00121	mg/kg	
	Environment - soil		PNEC	0,00184	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,2	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,2	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,3	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1,3	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,4	mg/kg	

Page 7 of 16  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 17.07.2020 / 0004  
Replacing version dated / version: 22.03.2018 / 0003  
Valid from: 17.07.2020  
PDF print date: 22.07.2020  
Pflege- und Korrosionsschutzöl 5 L  
Art.: 20760

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).  
(11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
Applies only if maximum permissible exposure values are listed here.  
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
These are specified by e.g. BS EN 14042.  
BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
Chemical resistant protective gloves (EN 374).  
If applicable  
Protective Neoprene® / polychloroprene gloves (EN 374).  
Protective nitrile gloves (EN 374).  
Minimum layer thickness in mm:  
0,5  
Permeation time (penetration time) in minutes:  
480  
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
The recommended maximum wearing time is 50% of breakthrough time.  
Protective hand cream recommended.

Skin protection - Other:  
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
Normally not necessary.  
With oil mist formation:  
Filter A P2 (EN 14387), code colour brown, white  
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
Not applicable

Additional information on hand protection - No tests have been performed.  
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
Selection of materials derived from glove manufacturer's indications.



Page 8 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.07.2020 / 0004  
 Replacing version dated / version: 22.03.2018 / 0003  
 Valid from: 17.07.2020  
 PDF print date: 22.07.2020  
 Pflege- und Korrosionsschutzöl 5 L  
 Art.: 20760

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Brown
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,914 g/ml (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Not determined
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	252,06 mm <sup>2</sup> /s (20°C)
Explosive properties:	Product is not explosive.
Oxidising properties:	No

### 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

Strong heat

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information



Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 17.07.2020 / 0004

Replacing version dated / version: 22.03.2018 / 0003

Valid from: 17.07.2020

PDF print date: 22.07.2020

Pflege- und Korrosionsschutzöl 5 L

Art.: 20760

## 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

### Pflege- und Korrosionsschutzöl 5 L

Art.: 20760

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

### Distillates (petroleum), hydrotreated light naphthenic

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:					OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	100				No indications of such an effect.
Aspiration hazard:						Yes
Other information:	NOAEL	>2000	mg/kg	Rat	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	

### Mixture of benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	

Page 10 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.07.2020 / 0004  
 Replacing version dated / version: 22.03.2018 / 0003  
 Valid from: 17.07.2020  
 PDF print date: 22.07.2020  
 Pflege- und Korrosionsschutzöl 5 L  
 Art.: 20760

Acute toxicity, by inhalation:	LD50	>1,9	mg/l/4h	Rat		Aerosol, Maximum achievable concentration., Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative

Isotridecanol, ethoxylated						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	300-2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative

Benzene, mono-C10-14-alkyl derivs., fractionation bottoms, intermediate cut, sulfonated, sodium salts						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit		Not irritantEPA OPPTS 870.2500
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (skin contact)

2,5-bis(octylidithio)-1,3,4-thiadiazole						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:				Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:				Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:				Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Respiratory or skin sensitisation:	EC3	1,2	%	Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Sensitising (skin contact)
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative

Page 11 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.07.2020 / 0004  
 Replacing version dated / version: 22.03.2018 / 0003  
 Valid from: 17.07.2020  
 PDF print date: 22.07.2020  
 Pflege- und Korrosionsschutzoeel 5 L  
 Art.: 20760

Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Effects on fertility):				Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	Negative

Di-iso-octyl amino methyl tolutriazole						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3313	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	(Draize-Test)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	(Draize-Test)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (skin contact)
Germ cell mutagenicity:				Mammalian	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Pflege- und Korrosionsschutzoeel 5 L Art.: 20760							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

Distillates (petroleum), hydrotreated light naphthenic							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	14d	>1000	mg/l	Oncorhynchus mykiss	QSAR	
12.3. Bioaccumulative potential:	BCF		<500				Low
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	

Page 12 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.07.2020 / 0004  
 Replacing version dated / version: 22.03.2018 / 0003  
 Valid from: 17.07.2020  
 PDF print date: 22.07.2020  
 Pflege- und Korrosionsschutzöl 5 L  
 Art.: 20760

12.2. Persistence and degradability:		28d	10	%			Not readily biodegradable
12.2. Persistence and degradability:							Mechanical precipitation possible.
12.2. Persistence and degradability:		28d	31	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily but inherent biodegradable.
12.3. Bioaccumulative potential:	Log Pow		6,0				A notable biological accumulation potential has to be expected (LogPow > 3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Water solubility:							Insoluble

**Mixture of benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	EC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	8	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	BCF		70,8				Not to be expected

**Isotridecanol, ethoxylated**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1 -< 10	mg/l	Cyprinus caprio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	1 -< 10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	1 -< 10	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	>60	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable

**Benzene, mono-C10-14-alkyl derivs., fractionation bottoms, intermediate cut, sulfonated, sodium salts**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
-------------------	----------	------	-------	------	----------	-------------	-------

Page 13 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.07.2020 / 0004  
 Replacing version dated / version: 22.03.2018 / 0003  
 Valid from: 17.07.2020  
 PDF print date: 22.07.2020  
 Pflege- und Korrosionsschutzöl 5 L  
 Art.: 20760

12.2. Persistence and degradability:		28d	8	%	activated sludge	OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Not biodegradable
12.3. Bioaccumulative potential:	Log Pow		6,75				A notable biological accumulation potential has to be expected (LogPow > 3).
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	

#### Di-iso-octyl amino methyl toluotriazole

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1,3	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	2,05	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	0,976	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,658	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:		28d	<10	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable CO <sub>2</sub> formation of the theoretical value
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

12 01 07 mineral-based machining oils free of halogens (except emulsions and solutions)

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

#### For contaminated packing material

Page 14 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.07.2020 / 0004  
 Replacing version dated / version: 22.03.2018 / 0003  
 Valid from: 17.07.2020  
 PDF print date: 22.07.2020  
 Pflege- und Korrosionsschutzöl 5 L  
 Art.: 20760

Pay attention to local and national official regulations.  
 Empty container completely.  
 Untamminated packaging can be recycled.  
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number: n.a.

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

### Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 0 %

### REGULATION (EC) No 648/2004

n.a.

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections:

2, 3, 8, 11, 12, 15

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.07.2020 / 0004  
 Replacing version dated / version: 22.03.2018 / 0003  
 Valid from: 17.07.2020  
 PDF print date: 22.07.2020  
 Pflege- und Korrosionsschutzöl 5 L  
 Art.: 20760

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H317 May cause an allergic skin reaction.  
 H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H400 Very toxic to aquatic life.  
 H411 Toxic to aquatic life with long lasting effects.

Eye Irrit. — Eye irritation  
 Asp. Tox. — Aspiration hazard  
 Skin Sens. — Skin sensitization  
 Acute Tox. — Acute toxicity - oral  
 Eye Dam. — Serious eye damage  
 Skin Irrit. — Skin irritation  
 Aquatic Acute — Hazardous to the aquatic environment - acute  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ASTM ASTM International (American Society for Testing and Materials)  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BSEF The International Bromine Council  
 bw body weight  
 CAS Chemical Abstracts Service  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EC European Community  
 ECHA European Chemicals Agency  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 etc. et cetera  
 EU European Union  
 EVAL Ethylene-vinyl alcohol copolymer  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential



Page 16 of 16  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 17.07.2020 / 0004  
Replacing version dated / version: 22.03.2018 / 0003  
Valid from: 17.07.2020  
PDF print date: 22.07.2020  
Pflege- und Korrosionsschutzöl 5 L  
Art.: 20760

IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC (Code) International Bulk Chemical (Code)  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCLID International Uniform Chemical Information Database  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PBT persistent, bioaccumulative and toxic  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
ppm parts per million  
PVC Polyvinylchloride  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC Substances of Very High Concern  
Tel. Telephone  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.