

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L US
Revision date : 22.07.2020
Print date : 28.07.2020

Version (Revision) : 3.0.0 (2.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

PROLAQ L US

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

PC 35 - Washing and cleaning products

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Bio-Circle Surface Technology GmbH

Street : Berensweg 200

Postal code/city : 33334 Gütersloh

Telephone : +49 5241 9443 0

Telefax : +49 5241 9443 44

Information contact : labor@bio-circle.de

1.4 Emergency telephone number

+49 5241 9443 51 during normal office hours

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Exclamation mark (GHS07)

Signal word

Warning

Hazard statements

H319 Causes serious eye irritation.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

1-butylpyrrolidin-2-one ; REACH No. : 01-2120062728-48-XXXX ; EC No. : 222-437-8; CAS No. : 3470-98-2

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L US
Revision date : 22.07.2020
Print date : 28.07.2020

Version (Revision) : 3.0.0 (2.0.0)

Weight fraction : $\geq 5 - < 10 \%$
Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319
BENZYL ALCOHOL ; REACH No. : 01-2119492630-38-XXXX ; EC No. : 202-859-9; CAS No. : 100-51-6
Weight fraction : $\geq 5 - < 10 \%$
Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Acute Tox. 4 ; H332 Eye Irrit. 2 ; H319
POTASSIUM CUMENESULFONATE ; REACH No. : 01-2119489427-24-XXXX ; EC No. : 629-764-9; CAS No. : 164524-02-1
Weight fraction : $\geq 1 - < 5 \%$
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319
SODIUM CUMENESULPHONATE ; REACH No. : 01-2119489411-37-XXXX ; EC No. : 239-854-6; CAS No. : 15763-76-5
Weight fraction : $\geq 1 - < 5 \%$
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

Following inhalation

Remove casualty to fresh air and keep warm and at rest.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Rub greasy ointment into the skin.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

After ingestion

Rinse mouth thoroughly with water. Let 1 glass of water be drunken in little sips (dilution effect). Do NOT induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Extinguishing powder Carbon dioxide (CO₂) Sand Nitrogen Extinguishing blanket

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide , Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

5.4 Additional information

The product itself does not burn. Co-ordinate fire-fighting measures to the fire surroundings.

Trade name : PROLAQ L US
Revision date : 22.07.2020
Print date : 28.07.2020

Version (Revision) : 3.0.0 (2.0.0)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Special danger of slipping by leaking/spilling product.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3 Methods and material for containment and cleaning up

Clear spills immediately. Wipe up with absorbent material (eg. cloth, fleece). Wash with plenty of water. Treat the recovered material as prescribed in the section on waste disposal.

6.4 Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep container tightly closed.

7.2 Conditions for safe storage, including any incompatibilities

Keep/Store only in original container. Protect against Frost

Hints on joint storage

Storage class (TRGS 510) : 12

7.3 Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

BENZYL ALCOHOL ; CAS No. : 100-51-6

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 5 ppm / 22 mg/m³

Peak limitation : 2(I)

Remark : H, Y

Version : 29.03.2019

DNEL-/PNEC-values

DNEL/DMEL

Limit value type : DNEL worker (systemic) (BENZYL ALCOHOL ; CAS No. : 100-51-6)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 90 mg/m³

Limit value type : DNEL worker (systemic) (BENZYL ALCOHOL ; CAS No. : 100-51-6)

Exposure route : Inhalation

Exposure frequency : Short-term

Limit value : 450 mg/m³

Limit value type : DNEL worker (systemic) (BENZYL ALCOHOL ; CAS No. : 100-51-6)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 9,5 mg/kg

Limit value type : DNEL worker (systemic) (BENZYL ALCOHOL ; CAS No. : 100-51-6)

Exposure route : Dermal

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L US
Revision date : 22.07.2020
Print date : 28.07.2020

Version (Revision) : 3.0.0 (2.0.0)

Exposure frequency : Short-term
Limit value : 47 mg/kg
Limit value type : DNEL worker (systemic) (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 53,6 mg/m³
Limit value type : DNEL worker (systemic) (SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 53,6 mg/m³
Limit value type : DNEL worker (systemic) (SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 7,6 mg/kg
Limit value type : DNEL worker (systemic) (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 7,6 mg/kg

8.2 Exposure controls

Personal protection equipment

Eye/face protection



Wear suitable safety goggles in case of splash.

Suitable eye protection

EN 166.

Skin protection

Hand protection



Wear protective gloves in case of longer lasting skin contact.

Suitable gloves type : EN 374.

Suitable material : NBR (Nitrile rubber)

Breakthrough time (maximum wearing time) : 480 min.

Thickness of the glove material : 0.4 mm

Remark : The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Respiratory protection



Respiratory protection necessary at: exceeding exposure limit values

Suitable respiratory protection apparatus

Combination filtering device (EN 14387)

Type : A

Remark

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L US
Revision date : 22.07.2020
Print date : 28.07.2020

Version (Revision) : 3.0.0 (2.0.0)

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

General information

Do not put any product-impregnated cleaning rags into your trouser pockets. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. P362+P364 - Take off contaminated clothing and wash it before reuse. P264 - Wash hands thoroughly after handling.

8.3 Additional information

No tests have been performed. Selection made for preparations according to the best available knowledge and information on ingredients. In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid

Colour : colourless

Odour

characteristic

Safety characteristics

Initial boiling point and boiling range (1013 hPa)	approx.	100	°C	
Flash point :				not applicable
Lower explosion limit :				not determined
Upper explosion limit :				not determined
Vapour pressure :	(50 °C)			not relevant
Density :	(20 °C)	approx.	1,02	g/cm ³
Solvent separation test :	(20 °C)			not relevant
pH :		approx.	7	
Flow time :	(20 °C)			not relevant
Maximum VOC content (EC) :			10	Wt %
Maximum VOC content (Switzerland) :			10	Wt %

DIN-cup 4 mm

9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non-reactive under normal use conditions.

10.2 Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

No known hazardous decomposition products.
Decomposition products in case of fire: see section 5.

Trade name : PROLAQ L US
Revision date : 22.07.2020
Print date : 28.07.2020

Version (Revision) : 3.0.0 (2.0.0)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute oral toxicity

Parameter : LD50 (1-butylpyrrolidin-2-one ; CAS No. : 3470-98-2)
Exposure route : Oral
Species : Rat
Effective dose : 500 mg/kg
Parameter : LD50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route : Oral
Species : Rat
Effective dose : 1230 - 1620 mg/kg
Parameter : LD50 (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
Exposure route : Oral
Species : Rat
Effective dose : > 2000 mg/kg
Parameter : LD50 (SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5)
Exposure route : Oral
Species : Rat
Effective dose : > 2000 mg/kg

Acute dermal toxicity

Parameter : LD50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route : Dermal
Species : Rabbit
Effective dose : 2000 mg/kg
Parameter : LD50 (SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5)
Exposure route : Dermal
Species : Rat
Effective dose : > 2000 mg/kg

Acute inhalation toxicity

Parameter : LC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route : Inhalation
Species : Rat
Effective dose : > 4178 mg/m³
Exposure time : 4 h
Method : OECD 403
Parameter : LC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route : Inhalation
Species : Rat
Effective dose : 1000 ppm
Exposure time : 8 h
Parameter : LC50 (SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5)
Exposure route : Inhalation
Species : Rat
Effective dose : > 5 mg/l
Exposure time : 4 h

Corrosion

Skin corrosion/irritation

No further relevant information available.

Serious eye damage/eye irritation

No further relevant information available.

Respiratory or skin sensitisation

Skin sensitisation

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L US
Revision date : 22.07.2020
Print date : 28.07.2020

Version (Revision) : 3.0.0 (2.0.0)

No further relevant information available.

Sensitisation to the respiratory tract

No further relevant information available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

No further relevant information available.

Germ cell mutagenicity

No further relevant information available.

Reproductive toxicity

No further relevant information available.

STOT-single exposure

No further relevant information available.

STOT-repeated exposure

No further relevant information available.

Aspiration hazard

No further relevant information available.

11.2 Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

11.3 Other adverse effects

Has degreasing effect on the skin. Frequently or prolonged contact with skin may cause dermal irritation.

11.4 Additional information

Preparation not tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : LC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)

Species : Fish

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : 460 mg/l

Exposure time : 96 h

Method : OECD 203

Parameter : LC0 (BENZYL ALCOHOL ; CAS No. : 100-51-6)

Species : Daphnia

Evaluation parameter : Acute (short-term) daphnia toxicity

Effective dose : 360 mg/l

Exposure time : 48 h

Parameter : LC50 (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)

Species : Cyprinus carpio (Common Carp)

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : > 100 mg/l

Exposure time : 96 h

Parameter : LC50 (SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5)

Species : Cyprinus carpio (Common Carp)

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : > 100 mg/kg

Exposure time : 96 h

Acute (short-term) toxicity to crustacea

Parameter : EC50 (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)

Species : Daphnia magna (Big water flea)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L US
Revision date : 22.07.2020
Print date : 28.07.2020

Version (Revision) : 3.0.0 (2.0.0)

Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : > 100 mg/l
Exposure time : 48 h

Chronic (long-term) toxicity to crustacea

Parameter : NOEC (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Chronic (long-term) daphnia toxicity
Effective dose : 51 mg/l
Exposure time : 21 D
Method : OECD 211

Acute (short-term) toxicity to aquatic algae and cyanobacteria

Parameter : EC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : 230 mg/l
Exposure time : 48 h
Method : OECD 202

Parameter : EC50 (SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : > 100 mg/l
Exposure time : 48 h

Parameter : EC50 (SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5)
Species : Desmodesmus subspicatus
Evaluation parameter : Acute (short-term) algae toxicity
Effective dose : > 100 mg/l
Exposure time : 72 h

Parameter : EC50 (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
Species : Desmodesmus subspicatus
Evaluation parameter : Acute (short-term) algae toxicity
Effective dose : > 100 mg/l
Exposure time : 72 h

Toxicity to microorganisms

Parameter : EC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Species : Bacteria toxicity
Effective dose : > 658 mg/l
Exposure time : 16 h

Parameter : EC50 (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
Species : Bacteria toxicity
Effective dose : > 1000 mg/l
Exposure time : 3 h

Parameter : EC50 (SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5)
Species : Bacteria toxicity
Effective dose : > 1000 mg/l

12.2 Persistence and degradability

Biodegradation

Parameter : Biodegradation (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Inoculum : Biodegradation
Degradation rate : 95 - 97 %
Test duration : 21 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301A

Parameter : Biodegradation (POTASSIUM CUMENESULFONATE ; CAS No. : 164524-02-1)
Inoculum : Biodegradation
Evaluation parameter : Aerobic

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L US
Revision date : 22.07.2020
Print date : 28.07.2020

Version (Revision) : 3.0.0 (2.0.0)

Degradation rate : 99,8 %
Test duration : 28 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301B
Parameter : Biodegradation (SODIUM CUMENESULPHONATE ; CAS No. : 15763-76-5)
Inoculum : Biodegradation
Evaluation parameter : Aerobic
Degradation rate : 99,8 %
Test duration : 28 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301B

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

None

SECTION 13: Disposal considerations

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. List of proposed waste codes/waste designations in accordance with EWC

13.1 Waste treatment methods

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

08 01 21* - Farb- oder Lackentfernerabfälle

Waste code packaging

15 01 02 - plastic packaging.

Waste treatment options

Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Handle contaminated packages in the same way as the substance itself.

13.2 Additional information

These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L US
Revision date : 22.07.2020
Print date : 28.07.2020

Version (Revision) : 3.0.0 (2.0.0)

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No transport as bulk according to IBC Code.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Use restriction according to REACH annex XVII, no. : 3

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations (EU)

Labelling for contents according to regulation (EC) No. 648/2004

< 5 % anionic surfactants

5 - 15 % non-ionic surfactants

< 5 % cationic surfactants

National regulations

AT: Labelling according to Austrian regulations (Chemikaliengesetz/ChemV).

CH: Chemikalienverordnung (ChemV) and Chemikalien-Risikoreduktions-Verordnung (Chem RRV) are complied.

Water hazard class (WGK)

Classification according to AwSV - Class : 2 (Obviously hazardous to water)

15.2 Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

03. Hazardous ingredients · 03. Further ingredients · 08. Occupational exposure limit values · 15. Restrictions on use

16.2 Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (Europäisches Übereinkommen über die Beförderung gefährlicher Güter auf der Straße)

AOX: adsorbierbare organisch gebundene Halogene

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

CAS: Chemical Abstracts Service (Unterabteilung der American Chemical Society)

CLP: Verordnung (EG) Nr. 1272/2008 über die Einstufung, Kennzeichnung und Verpackung von Stoffen und Gemischen (Classification Labelling and Packaging)

EAK / AVV: europäischer Abfallartenkatalog / Abfallverzeichnis-Verordnung

ECHA: Europäische Chemikalienagentur (European Chemicals Agency)

EINECS: : Altstoffverzeichnis (European Inventory of Existing Commercial Chemical Substances)

GHS: Global harmonisiertes System zur Einstufung und Kennzeichnung von Chemikalien (Globally Harmonized System of Classification and Labelling of Chemicals)

IATA: Internationale Luftverkehrs-Vereinigung (International Air Transport Association)

ICAO: Internationale Zivilluftfahrtorganisation (International Civil Aviation Organization)

IMDG: Gefahrgutkennzeichnung für gefährliche Güter im Seeschiffverkehr (International Maritime Code for Dangerous Goods)

RID: Regelung zur internationalen Beförderung gefährlicher Güter im Schienenverkehr (Règlement concernant le

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : PROLAQ L US
Revision date : 22.07.2020
Print date : 28.07.2020

Version (Revision) : 3.0.0 (2.0.0)

transport international ferroviaire de marchandises dangereuses)
TRGS: Technische Regel für den Umgang mit Gefahrstoffen
VbF: Verordnung über brennbare Flüssigkeiten
VOC: flüchtige organische Verbindung (volatile organic compound)
VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe
WGK: Wassergefährdungsklasse

16.3 Key literature references and sources for data

DGUV: GESTIS-Stoffdatenbank
ECHA: Classification And Labelling Inventory
ECHA: Pre-registered Substances
ECHA: Registered Substances
EC_Safety Data Sheet of Suppliers
ESIS: European Chemical Substances Information System
GDL: Gefahrstoffdatenbank der Länder
UBA Rigoletto: Wassergefährdende Stoffe
Regulation (EC) No. 1907/2006 of the European Parliament and of the Council
Regulation (EC) No. 1272/2008 of the European Parliament and of the Council

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.