

Technical data sheet



Neutral cross-linking silicone joint sealant

Elastic, odorless silicone joint sealant with fungicidal properties, lightfast, resistant to cleaning agents and reactive with humidity.

Advantages & Features

Odorless
Lightfast
Elastic
Detergent resistant
Color: transparent, white, gray antifungal
Very good adhesion to wood, glass, acrylic, ceramics, enamel, concrete, stainless steel
Skin formation approx. 10 min
Hardening approx. 2mm per day
Processing temperature: +5°C to +40°C
Temperature range: -40°C to +150°C

Application areas

For sealing especially in sanitary and wet rooms, in the kitchen area and for add-on furniture, also suitable for acrylic.

Tests and Approvals

./.

Application

The adhesive surfaces must be dry, clean and free from loose parts. Adhesion without primer on glass, enamel, acrylic, tiles, glazed ceramics. Any subsequent smoothing must be done before the skin forms. In the case of substrates such as marble, granite or similar building materials, soiling can occur at the edges.

Shorten/cut at an angle depending on the required sealing cross-section. Apply a strip of tape to both sides of the seal. Apply the sealant and smooth the seal with a suitable tool (Fugenboy). Remove strips of tape.

Shelf life and storage

15 months in the original sealed container. Storage temperature cool and dry.

Order number, article and packing unit

Order-no.	Article	PU
16001	310 ml cartridge white	12
16002	310 ml cartridge grey - manhattan	12
16003	310 ml cartridge transparent	12
16009	280 ml cartridge grey-anthrazit	12
16060	100 ml tube white	8
16061	100 ml tube grey-manhattan	8
16062	100 ml tube transparent	8

Notice

All information and recommendations contained in this technical data sheet do not represent guaranteed properties. They are based on our research results and experience. However, they are non-binding as we are not responsible for compliance with the processing conditions may be, since we do not know the special application conditions at the user.

A guarantee can only be given for the consistently high quality of our products. We recommend that you conduct sufficient tests to determine whether the specified product has the properties you want. A claim from this is excluded. The processor bears sole responsibility for incorrect or inappropriate use.

Safety and health

See safety data sheet.

