

# Instructions

## Dust protection



Georg Schmieder GmbH&Co  
 Julius-Hölder-Str. 8  
 70597 Stuttgart Degerloch  
 Fon 0711/13269-800, Fax 0711/13269-50  
 info@werkzeuge-mit-ideen.de  
 www.werkzeuge-mit-ideen.de

### Before using:

A) Please check the delivery immediately upon receipt by the forwarding agent on damages in transit and completeness.

B) The door handle is in the fastened foil bag with

### Montage:

C) The complete door element (1) consisting of doorframes and door must be putting in the front of the door case.

The frame can be mounting directly in the door case or if higher necessary on the ceiling (max. 275 cm).

If the door case is smaller than 195 cm please clamp the door only on the ceiling.

To reach the self shutdown of the door please clamp the above clip some cm behind (crossed from the lower clip). If the door is mounting in straight line – it does not closed itself.

By using the thumb pressure (above the telescope angle) you get the tensely you need (2+3). Also you can lose this by pressing the same clip (4).

D) The Proofing (5)

In the scope of delivery there are 2 tapes contained:

a) Double sided Tape brown soft (L20.623.010)

b) Smooth-Tape one side yellow (L20.622) – as

underground

### Removing

Take off the tape carefully.

Release the telescope angles like Pic. 4.

Attention: Risk of injure – by loosing the construction not carefully – it can fall down



2



Tensioning

3



Releasing

4



5



### Scope of Delivery:

No:

1 Door element with frame complete

Z02.040

1 Door handle with countersunk (foil bag)

Item-