

Page 1 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2020 / 0016

Replacing version dated / version: 03.07.2019 / 0015

Valid from: 18.05.2020 PDF print date: 18.05.2020

Motorbike 4T Synth 10 W-50 Race 1 L

Art.: 1502

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Motorbike 4T Synth 10 W-50 Race 1 L

Art.: 1502

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Motor oil

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC17 - Hydraulic fluids

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC20 - Use of functional fluids in small devices

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 9a - Widespread use of functional fluid (indoor)

ERC 9b - Widespread use of functional fluid (outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr

Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification



Page 2 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2020 / 0016

Replacing version dated / version: 03.07.2019 / 0015

Valid from: 18.05.2020

PDF print date: 18.05.2020

Motorbike 4T Synth 10 W-50 Race 1 L

Art.: 1502

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange.

Hazardous to drinking water, on escape of even small quantities.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3.2 Mixture

Baseoil - unspecified *	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1. H304

Distillates (petroleum), hydrotreated light paraffinic	
Registration number (REACH)	01-2119487077-29-XXXX
Index	649-468-00-3
EINECS, ELINCS, NLP	265-158-7
CAS	64742-55-8
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Bis(nonylphenyl)amine	
Registration number (REACH)	01-2119488911-28-XXXX
Index	
EINECS, ELINCS, NLP	253-249-4
CAS	36878-20-3
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Chronic 4, H413

Impurities, test data and additional information may have been taken into account in classifying and labelling the product. For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

* The contained mineral oil can be described by one or more of the following numbers:

EINECS, ELINCS, NLP	Registration number (REACH)	Chemical name
265-157-1	01-2119484627-25-XXXX	Distillates (petroleum), hydrotreated heavy paraffinic
265-158-7	01-2119487077-29-XXXX	Distillates (petroleum), hydrotreated light paraffinic
265-169-7	01-2119471299-27-XXXX	Distillates (petroleum), solvent-dewaxed heavy paraffinic



Page 3 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2020 / 0016

Replacing version dated / version: 03.07.2019 / 0015

Valid from: 18.05.2020 PDF print date: 18.05.2020

Motorbike 4T Synth 10 W-50 Race 1 L

Art.: 1502

265-159-2 01-2119480132-48-XXXX

Distillates (petroleum), solvent-dewaxed light paraffinic

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Irritation of the eyes

with long-term contact:

Drying of the skin.

Irritation of the skin.

With oil mist formation:

Irritation of the respiratory tract

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO2

Foam

Dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Carbon dioxide

Oxides of phosphorus

Oxides of sulphur

Oxides of nitrogen

Toxic gases

Hot product gives off combustible vapours.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.



Œ

Page 4 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2020 / 0016

Replacing version dated / version: 03.07.2019 / 0015

Valid from: 18.05.2020 PDF print date: 18.05.2020

Motorbike 4T Synth 10 W-50 Race 1 L

Art.: 1502

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of oil mist.

Remove possible causes of ignition - do not smoke.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13. Oil binder

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid formation of oil mist.

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Do not heat to temperatures close to flash point.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Protect against moisture and store closed.

Do not store over 60°C.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Oil mist, mineral		Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, e	xcluding metal WEL-STEL:		
working fluids, ACGIH)			
Monitoring procedures:	- Draeger - Oil M	1ist 1/a (67 33 031)	



Œ

Page 5 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2020 / 0016

Replacing version dated / version: 03.07.2019 / 0015

Valid from: 18.05.2020 PDF print date: 18.05.2020

Motorbike 4T Synth 10 W-50 Race 1 L

Art.: 1502

BMGV: --- Other information: ---

Distillates (petroleum), hydrotreated light paraffinic								
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note		
	Environment - oral (animal feed)		PNEC	9,33	mg/kg feed			
Consumer	Human - inhalation	Long term, local effects	DNEL	1,19	mg/m3			
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg bw/day			
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,97	mg/kg bw/day			
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,7	mg/m3			

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	0,1	mg/l	
	Environment - marine		PNEC	0,01	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	1	mg/l	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - sediment, freshwater		PNEC	132000	mg/kg dw	
	Environment - sediment, marine		PNEC	13200	mg/kg dw	
	Environment - soil		DNEL	263000	mg/kg dw	
	Environment - periodic release		PNEC	1	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,31	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,09	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,31	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,62	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4,37	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

8.2 Exposure controls

^{(8) =} Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit

^{(8) =} Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU), 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

^{** =} The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

^{(13) =} The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).



Page 6 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2020 / 0016 Replacing version dated / version: 03.07.2019 / 0015

Valid from: 18.05.2020 PDF print date: 18.05.2020

Motorbike 4T Synth 10 W-50 Race 1 L

Art.: 1502

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eve/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective gloves, oil resistant (EN 374).

If applicable

Protective Neoprene® / polychloroprene gloves (EN 374).

Protective nitrile gloves (EN 374).

Protective PVC gloves (EN 374).

Minimum layer thickness in mm:

0.4

Permeation time (penetration time) in minutes:

The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

Respiratory protection:

Normally not necessary.

With oil mist formation:

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties



Page 7 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2020 / 0016

Replacing version dated / version: 03.07.2019 / 0015

Valid from: 18.05.2020 PDF print date: 18.05.2020

Motorbike 4T Synth 10 W-50 Race 1 L

Art.: 1502

Physical state: Liquid Colour: Brown Odour: Characteristic Odour threshold: Not determined pH-value: Not determined Melting point/freezing point: Not determined Initial boiling point and boiling range: Not determined Flash point: 230 °C Evaporation rate: Not determined

Flammability (solid, gas): n.a.

Not determined Lower explosive limit: Upper explosive limit: Not determined Vapour pressure: Not determined Vapour density (air = 1): Not determined Density: 0,844 g/ml Bulk density: n.a.

Solubility(ies): Not determined Water solubility: Insoluble Partition coefficient (n-octanol/water): Not determined Auto-ignition temperature: Not determined

Decomposition temperature: Not determined Viscosity: 123,5 mm2/s (40°C) 18,48 mm2/s (100°C) Viscosity: Explosive properties: Product is not explosive.

Oxidising properties:

9.2 Other information

Miscibility: Not determined Fat solubility / solvent: Not determined Conductivity: Not determined Surface tension: Not determined Solvents content: Not determined

SECTION 10: Stability and reactivity

Nο

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Motorbike 4T Synth 10 W-50 Ra	ice 1 L					
Art.: 1502						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.



Page 8 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.05.2020 / 0016

Replacing version dated / version: 03.07.2019 / 0015

Valid from: 18.05.2020 PDF print date: 18.05.2020

Motorbike 4T Synth 10 W-50 Race 1 L Art.: 1502

Respiratory or skin			n.d.a.
sensitisation:			
Germ cell mutagenicity:			n.d.a.
Carcinogenicity:			n.d.a.
Reproductive toxicity:			n.d.a.
Specific target organ toxicity -			n.d.a.
single exposure (STOT-SE):			
Specific target organ toxicity -			n.d.a.
repeated exposure (STOT-RE):			
Aspiration hazard:			n.d.a.
Symptoms:			n.d.a.

Distillates (petroleum), hydrotr		raffinic				
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Carcinogenicity:				Mouse	OECD 451 (Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:				Rat	OECD 421 (Reproduction/Developm ental Toxicity Screening Test)	Negative, Analogous conclusion
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Aspiration hazard:						Yes
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	125	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	1000	mg/kg	Rabbit	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	Analogous conclusion

Bis(nonylphenyl)amine						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
					Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	Analogous
					Dermal Toxicity)	conclusion



Page 9 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.05.2020 / 0016

Replacing version dated / version: 03.07.2019 / 0015

Valid from: 18.05.2020 PDF print date: 18.05.2020

Motorbike 4T Synth 10 W-50 Race 1 L Art.: 1502

Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Analogous
					Irritation/Corrosion)	conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant,
					Irritation/Corrosion)	Analogous
						conclusion
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact),
						Analogous
						conclusion
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
				typhimurium	Reverse Mutation Test)	Analogous
						conclusion
Germ cell mutagenicity:				Mouse	OECD 478 (Genetic	Negative,
					Toxicology - Rodent	Analogous
					dominant Lethal Test)	conclusion
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative,
					Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	
Reproductive toxicity	NOAEL	150	mg/kg	Rat	OECD 414 (Prenatal	Negative
(Developmental toxicity):			bw/d		Developmental Toxicity	
					Study)	
Specific target organ toxicity -	NOAEL	<100	mg/kg	Rat	OECD 408 (Repeated	
repeated exposure (STOT-RE),			bw/d		Dose 90-Day Oral	
oral:					Toxicity Study in	
					Rodents)	

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Isolate as much as possible with an oil separator.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Other adverse							n.d.a.
effects:							

Distillates (petroleum), hydrotreated light paraffinic								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)		
12.1. Toxicity to fish:	NOEC/NOEL	28d	>1000	mg/l	Oncorhynchus mykiss	QSAR		
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion	
12.1. Toxicity to fish:	NOEC/NOEL	14d	1000	mg/l	Oncorhynchus mykiss	QSÁR		
12.3. Bioaccumulative potential:							Not to be expected	



Page 10 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.05.2020 / 0016

Replacing version dated / version: 03.07.2019 / 0015

Valid from: 18.05.2020 PDF print date: 18.05.2020

Motorbike 4T Synth 10 W-50 Race 1 L Art.: 1502

12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute	Analogous conclusion
						Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	31	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable, Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		>6				@20°C
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Bis(nonylphenyl)amine							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to algae:	NOEC/NOEL	72h	>10	mg/l	Desmodesmus subspicatus		Analogous conclusion
12.2. Persistence and degradability:		28d	24	%	·	OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Not readily biodegradable
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	600	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	1	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable, Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		>7,6				Concentration in organisms possible.
12.3. Bioaccumulative potential:	BCF		1730				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion



(B)

Page 11 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2020 / 0016

Replacing version dated / version: 03.07.2019 / 0015

Valid from: 18.05.2020 PDF print date: 18.05.2020

Motorbike 4T Synth 10 W-50 Race 1 L

Art.: 1502

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LQ:n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name: 14.3. Transport hazard class(es):

14.3. Transport nazard class(es):

14.4. Packing group:

Marine Pollutant:

n.a.

14.5. Environmental hazards:

Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):
14.4. Packing group:

n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0 %



ദ

Page 12 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2020 / 0016

Replacing version dated / version: 03.07.2019 / 0015

Valid from: 18.05.2020 PDF print date: 18.05.2020

Motorbike 4T Synth 10 W-50 Race 1 L

Art.: 1502

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

3

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

Asp. Tox. — Aspiration hazard

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency
EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive



Page 13 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.05.2020 / 0016

Replacing version dated / version: 03.07.2019 / 0015

Valid from: 18.05.2020 PDF print date: 18.05.2020

Motorbike 4T Synth 10 W-50 Race 1 L

Art.: 1502

IUCLID International Uniform Chemical Information Database

LQ **Limited Quantities**

International Convention for the Prevention of Marine Pollution from Ships MARPOL

not applicable n.a. not available n.av. n.c. not checked n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org.

PBT persistent, bioaccumulative and toxic

PF Polyethylene

PNEC Predicted No Effect Concentration

parts per million ppm

PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No.

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Telephone Tel.

United Nations Recommendations on the Transport of Dangerous Goods UN RTDG

VOC Volatile organic compounds

very persistent and very bioaccumulative vPvB

wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.