

Page 1 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 15.04.2020 / 0016 Replacing version dated / version: 24.10.2019 / 0015 Valid from: 15.04.2020 PDF print date: 15.04.2020 Top Tec ATF 1200 5 L Art.: 3682

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

# **1.1 Product identifier**

ആ

# Top Tec ATF 1200 5 L Art.: 3682

# **1.2** Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Automatic transmission oil Sector of use [SU]: SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU21 - Consumer uses: Private households (=general public = consumers) SU22 - Professional uses: Public domain (administration, education, entertainment, ser

SU21 - Consumer uses: Private households (=general public = consumers) SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Chemical product category [PC]: PC17 - Hydraulic fluids PC24 - Lubricants, greases, release products Process category [PROC]: PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing) PROC20 - Use of functional fluids in small devices Article Categories [AC]: AC99 - Not required. Environmental Release Category [ERC]: ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC 7 - Use of functional fluid at industrial site ERC 9a - Widespread use of functional fluid (indoor) ERC 9b - Widespread use of functional fluid (outdoor) Uses advised against: No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

## 1.4 Emergency telephone number Emergency information services / official advisory body:

# Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

**SECTION 2: Hazards identification** 



Page 2 of 11

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 15.04.2020 / 0016 Replacing version dated / version: 24.10.2019 / 0015 Valid from: 15.04.2020 PDF print date: 15.04.2020 Top Tec ATF 1200 5 L Art.: 3682

# 2.1 Classification of the substance or mixtureClassification according to Regulation (EC) 1272/2008 (CLP)Hazard classHazard categoryHazard statementAquatic Chronic3H412-Harmful to aquatic life with long lasting effects.

# 2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)

H412-Harmful to aquatic life with long lasting effects.

P273-Avoid release to the environment. P501-Dispose of contents / container to an approved waste disposal facility.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange.

Hydrocarbons can be harmful to water.

Hazardous to drinking water, on escape of even small quantities.

# **SECTION 3: Composition/information on ingredients**

#### 3.1 Substance

#### n.a. 3.2 Mixture

Alkyl phosphites	
Registration number (REACH)	01-0000017126-75-XXXX
Index	
EINECS, ELINCS, NLP	424-820-7
CAS	
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H312
	Aquatic Acute 1, H400 (M=10)
	Aquatic Chronic 1, H410 (M=10)
	Skin Corr. 1B, H314
	Eye Dam. 1, H318

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected! Never pour anything into the mouth of an unconscious person!

# Inhalation

Remove person from danger area.



Page 3 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 15.04.2020 / 0016 Replacing version dated / version: 24.10.2019 / 0015 Valid from: 15.04.2020 PDF print date: 15.04.2020 Top Tec ATF 1200 5 L Art.: 3682

Supply person with fresh air and consult doctor according to symptoms.

# Skin contact

ആ

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

## Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting - give copious water to drink. Consult doctor immediately. Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. Irritation of the eyes With long-term contact: Drying of the skin. Dermatitis (skin inflammation) Oil acne Allergic reaction possible. On vapour formation: Irritation of the respiratory tract Ingestion: Nausea Vomiting Gastrointestinal disturbances **4.3 Indication of any immediate medical attention and special treatment needed** 

Symptomatic treatment.

**SECTION 5: Firefighting measures** 

# 5.1 Extinguishing media

#### Suitable extinguishing media

CO2 Extinction powder Foam

# Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Oxides of sulphur Toxic gases Oxides of nitrogen Flammable vapour/air mixtures

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

**SECTION 6: Accidental release measures** 

# 6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.



Page 4 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 15.04.2020 / 0016 Replacing version dated / version: 24.10.2019 / 0015 Valid from: 15.04.2020 PDF print date: 15.04.2020 Top Tec ATF 1200 5 L Art.: 3682

Avoid contact with eyes or skin. If applicable, caution - risk of slipping.

ആ

#### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Oil binder

Do not wash away with water or watery cleaning agents.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation. Avoid inhalation of the vapours. Avoid contact with eyes or skin. Do not carry cleaning cloths soaked in product in trouser pockets. Do not heat to temperatures close to flash point. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals. Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Do not store with oxidizing agents.

Impermeable floor.

Store in a well ventilated place. Protect from direct sunlight and warming.

#### 7.3 Specific end use(s)

No information available at present.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Chemical Name     Oil mist, mineral			Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal	WEL-STEL:		
working fluids, ACGIH)			
Monitoring procedures: -	Draeger - Oil Mist 1/a (67 33 031)		
BMGV:		Other information:	

Alkyl phosphites						
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					



Page 5 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 15.04.2020 / 0016 Replacing version dated / version: 24.10.2019 / 0015 Valid from: 15.04.2020 PDF print date: 15.04.2020 Top Tec ATF 1200 5 L Art.: 3682

ആ

Environment - freshwater	PNEC	0,036	mg/l
Environment - sediment,	PNEC	0,128	mg/kg
freshwater			
Environment - soil	PNEC	0,104	mg/kg

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).
(11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit

(8) = Innalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

# 8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Protective gloves, oil resistant (EN 374) If applicable Protective Neoprene® / polychloroprene gloves (EN 374). Protective nitrile gloves (EN 374). Minimum layer thickness in mm: 0,4 Permeation time (penetration time) in minutes: > 480 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective PVC gloves (EN 374) Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. With oil mist formation: Filter A2 P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.



Page 6 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 15.04.2020 / 0016 Replacing version dated / version: 24.10.2019 / 0015 Valid from: 15.04.2020 PDF print date: 15.04.2020 Top Tec ATF 1200 5 L Art.: 3682

Thermal hazards: Not applicable

ആ

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

## **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Red
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	230 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,85 g/ml
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	36,4 mm2/s (40°C)
Viscosity:	6,9 mm2/s (100°C)
Explosive properties:	Product is not explosive.
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

# **SECTION 10: Stability and reactivity**

10.1 Reactivity
The product has not been tested.

10.2 Chemical stability
Stable with proper storage and handling.

10.3 Possibility of hazardous reactions
No dangerous reactions are known.

10.4 Conditions to avoid
See also section 7.



Page 7 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 15.04.2020 / 0016 Replacing version dated / version: 24.10.2019 / 0015 Valid from: 15.04.2020 PDF print date: 15.04.2020 Top Tec ATF 1200 5 L Art.: 3682

# Strong heat **10.5 Incompatible materials**

(GB)·

See also section 7. Avoid contact with strong oxidizing agents. Avoid contact with strong acids.

# **10.6 Hazardous decomposition products**

See also section 5.2 No decomposition when used as directed.

# **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).
Top Tec ATF 1200 5 L

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Alkyl phosphites						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>500	mg/kg	Rabbit		

# SECTION 12: Ecological information

Top Tec ATF 1200 5 L							
Art.: 3682							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	-						n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability: 12.3. Bioaccumulative							Not readily but inherent biodegradable. Isolate as much as possible with an oil separator. n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.



Page 8 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 15.04.2020 / 0016 Replacing version dated / version: 24.10.2019 / 0015 Valid from: 15.04.2020 PDF print date: 15.04.2020 Top Tec ATF 1200 5 L Art.: 3682

# Alkyl phosphites

œ

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1,5	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EL50	48h	0,09	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,14	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	0,31	mg/l	Pseudokirchneriell a subcapitata		
12.2. Persistence and degradability:		28d	2,34	%			
12.3. Bioaccumulative potential:	Log Pow		0,28				
Water solubility:			0,71	mg/l			

# **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

# For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

#### **SECTION 14: Transport information**

General statements	
14.1. UN number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Marine Pollutant:	n.a
14.5. Environmental hazards:	Not applicable
Transport by air (IATA)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
14.5. Environmental hazards:	Not applicable



Page 9 of 11

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 15.04.2020 / 0016 Replacing version dated / version: 24.10.2019 / 0015 Valid from: 15.04.2020 PDF print date: 15.04.2020 Top Tec ATF 1200 5 L Art.: 3682

#### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code Non-dangerous material according to Transport Regulations.

**SECTION 15: Regulatory information** 

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions: Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

# **SECTION 16: Other information**

**Revised sections:** 

These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

#### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aquatic Chronic 3, H412	Classification based on test data.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects.

Aquatic Chronic - Hazardous to the aquatic environment - chronic Acute Tox. - Acute toxicity - dermal Aquatic Acute - Hazardous to the aquatic environment - acute Skin Corr. — Skin corrosion Eye Dam. — Serious eye damage

#### Any abbreviations and acronyms used in this document:

according, according to acc., acc. to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Article number Art., Art. no. ASTM ASTM International (American Society for Testing and Materials) Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BSEF The International Bromine Council

3, 8, 9, 11, 12

< 0,3 %





ആ Page 10 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 15.04.2020 / 0016 Replacing version dated / version: 24.10.2019 / 0015 Valid from: 15.04.2020 PDF print date: 15.04.2020 Top Tec ATF 1200 5 L Art.: 3682 bw body weight CAS Chemical Abstracts Service CI P Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level dry weight dw e.g. for example (abbreviation of Latin 'exempli gratia'), for instance ЕČ European Community ECHA European Chemicals Agency EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances **ELINCS** European List of Notified Chemical Substances FN European Norms EPA United States Environmental Protection Agency (United States of America) et cetera etc. EU **European Union** EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number general gen. GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential International Agency for Research on Cancer IARC International Air Transport Association ΙΑΤΑ IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. **IUCLID** International Uniform Chemical Information Database Limited Quantities 10 MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. n.av. not available not checked n.c. n.d.a. no data available OECD Organisation for Economic Co-operation and Development organic org. PBT persistent, bioaccumulative and toxic ΡE Polyethylene PNEC Predicted No Effect Concentration ppm parts per million PVC Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds very persistent and very bioaccumulative vPvB wet weight wwt The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

 $\ensuremath{\mathbb{C}}$  by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document



Page 11 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 15.04.2020 / 0016 Replacing version dated / version: 24.10.2019 / 0015 Valid from: 15.04.2020 PDF print date: 15.04.2020 Top Tec ATF 1200 5 L Art.: 3682

is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.