

Page 1 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.05.2019 / 0008 Replacing version dated / version: 18.10.2018 / 0007 Valid from: 08.05.2019 PDF print date: 10.05.2019 Top Tec ATF 1700 20 L Art.: 3695

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

ആ

Top Tec ATF 1700 20 L Art.: 3695

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Gear lubricant Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet (B)

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixtureClassification according to Regulation (EC) 1272/2008 (CLP)Hazard classHazard categoryHazard statementAquatic Chronic3H412-Harmful to act

H412-Harmful to aquatic life with long lasting effects.

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)

H412-Harmful to aquatic life with long lasting effects.

P273-Avoid release to the environment.

P501-Dispose of contents / container to an approved waste disposal facility.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0, 1 %).



Page 2 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.05.2019 / 0008 Replacing version dated / version: 18.10.2018 / 0007 Valid from: 08.05.2019 PDF print date: 10.05.2019 Top Tec ATF 1700 20 L Art.: 3695

Product can compose a film on the water surface, which can prevent oxygen exchange. Endangerment of potable water possible.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. **3.2 Mixtu<u>re</u>**

GB

Alkyl methacrylate, alkylaminoalkylmethacrylamide copolymer (ACC-	
LJ446756-22)	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Irrit. 2, H319
	Aquatic Chronic 4, H413

2,6-tert-butylphenol	
Registration number (REACH)	01-2119490822-33-XXXX
Index	
EINECS, ELINCS, NLP	204-884-0
CAS	128-39-2
content %	0,25-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	620-540-6 (REACH-IT List-No.)
CAS	1218787-32-6
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302
	Skin Corr. 1C, H314
	Eye Dam. 1, H318
	Aquatic Acute 1, H400 (M=10)
	Aquatic Chronic 1, H410 (M=1)

2 //C0 44 iss. C40 risk)slludeuu)mensen 4 smins	
3-((C9-11-iso, C10-rich)alkyloxy)propan-1-amine	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	939-485-7 (REACH-IT List-No.)
CAS	218141-16-3
content %	0,01-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302
	Skin Corr. 1B, H314
	Eye Dam. 1, H318
	Aquatic Acute 1, H400 (M=100)
	Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures



Page 3 of 12

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.05.2019 / 0008 Replacing version dated / version: 18.10.2018 / 0007 Valid from: 08.05.2019 PDF print date: 10.05.2019 Top Tec ATF 1700 20 L Art.: 3695

4.1 Description of first aid measures

First-aiders should ensure they are protected! Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Unsuitable cleaning product: Solvent Thinners

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. The following may occur: Irritation of the eyes With long-term contact: Drying of the skin. Dermatitis (skin inflammation) Oil acne Allergic reaction possible. On vapour formation: Irritation of the respiratory tract Indestion: Gastrointestinal disturbances Nausea Vomiting Blood count modifications Effects/damages the central nervous system In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media CO2 Extinction powder Water jet spray Large fire: Water jet spray / alcohol resistant foam Unsuitable extinguishing media
High volume water jet 5.2 Special hazards arising from the substance or mixture In case of fire the following can develop: Oxides of carbon Toxic pyrolysis products. Flammable vapour/air mixtures 5.3 Advice for firefighters In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply.



Page 4 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.05.2019 / 0008 Replacing version dated / version: 18.10.2018 / 0007 Valid from: 08.05.2019 PDF print date: 10.05.2019 Top Tec ATF 1700 20 L Art.: 3695

According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air. Avoid formation of oil mist. Avoid contact with eyes or skin. If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

അ

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13. Oil binder

Do not wash away with water or watery cleaning agents.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid formation of oil mist.

Ensure good ventilation. Keep away from sources of ignition - Do not smoke.

Do not heat to temperatures close to flash point.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing. Impermeable floor.

Protect against moisture and store closed.

Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters



Page 5 of 12

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.05.2019 / 0008 Replacing version dated / version: 18.10.2018 / 0007 Valid from: 08.05.2019 PDF print date: 10.05.2019 Top Tec ATF 1700 20 L Art.: 3695

Chemical Name	Oil mist, mineral			Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, o	excluding metal	WEL-STEL:		
working fluids, ACGIH)				
Monitoring procedures:	-	Draeger - Oil 10/a-P (67 28 371)		
	-	Draeger - Oil Mist 1/a (67 33 031)		
BMGV:			Other information:	-

2,6-tert-butylphenol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - marine		PNEC	0,00004 5	mg/l	
	Environment - freshwater		PNEC	0,001	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,67	mg/kg	
Consumer	Human - oral		DNEL	6,75	mg/kg bw/day	
Consumer	Human - inhalation		DNEL	20,9	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2,77	mg/kg	
Workers / employees	Human - dermal		DNEL	11,25	mg/kg bw/day	
Workers / employees	Human - inhalation		DNEL	70,61	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5,8	mg/m3	

Distillates (petroleum), hydrotreated heavy paraffinic									
Area of application	Exposure route / Effect on health Descriptor Value Unit Note								
	Environmental								
	compartment								
	Environment - oral (animal feed)		PNEC	9,33	mg/kg				

B WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.



Page 6 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.05.2019 / 0008 Replacing version dated / version: 18.10.2018 / 0007 Valid from: 08.05.2019 PDF print date: 10.05.2019 Top Tec ATF 1700 20 L Art.: 3695 Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing and protective equipment before entering areas in which food is consumed. Eve/face protection: Tight fitting protective goggles (EN 166) with side protection, with danger of splashes. Skin protection - Hand protection: Protective gloves, oil resistant (EN 374) If applicable Protective Neoprene® / polychloroprene gloves (EN 374). Protective nitrile gloves (EN 374). Minimum layer thickness in mm: 0.4 Permeation time (penetration time) in minutes: > 480Protective hand cream recommended. The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments). Respiratory protection: Normally not necessary. With oil mist formation: Filter A2 P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment. Thermal hazards: If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection). Additional information on hand protection - No tests have been performed. In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

ആ

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Brown
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	240 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,84 g/ml



Page 7 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.05.2019 / 0008 Replacing version dated / version: 18.10.2018 / 0007

œ

Revision date / version: 08.05.2019 / 0008 Replacing version dated / version: 18.10.2018 / 0007 Valid from: 08.05.2019 PDF print date: 10.05.2019 Top Tec ATF 1700 20 L Art.: 3695

Bulk density: Solubility(ies): Water solubility: Partition coefficient (n-octanol/water): Auto-ignition temperature: Decomposition temperature: Viscosity: Viscosity: Viscosity: Explosive properties: Oxidising properties:

9.2 Other information

Miscibility: Fat solubility / solvent: Conductivity: Surface tension: Solvents content: Not determined Not determined Insoluble Not determined Not determined 38 mm2/s (40°C) 7,7 mm2/s (100°C) Not determined Not determined

Not determined Not determined Not determined Not determined Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** Heating, open flame, ignition sources **10.5 Incompatible materials** Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products** No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Foxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	-					n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
2.6 tort hutulahanal						
2,6-tert-butylphenol Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes



Page 8 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.05.2019 / 0008 Replacing version dated / version: 18.10.2018 / 0007 Valid from: 08.05.2019 PDF print date: 10.05.2019 Top Tec ATF 1700 20 L Art.: 3695

œ

Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	10000	mg/kg	Rabbit		
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Symptoms:						burns, nausea and vomiting., sore throat, stomach pain
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	100	mg/kg bw/d	Rat		Target organ(s): liver

3-((C9-11-iso, C10-rich)alkyloxy)propan-1-amine							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	300-2000	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	Female	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Corr. 1B	

SECTION 12: Ecological information

Top Tec ATF 1700 20 L							
Art.: 3695							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							Isolate as much
degradability:							as possible with
-							an oil separator.
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Other adverse							n.d.a.
effects:							

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1,4	mg/l	Pimephales	OECD 204 (Fish,	
					promelas	Prolonged Toxicity	
						Test - 14-Day	
						Study)	
12.1. Toxicity to daphnia:	EC50	48h	0,45-0,8	mg/l	Daphnia magna	U.S. EPA	
						ECOTOX	
						Database	
12.1. Toxicity to daphnia:	LC50	21d	0,23	mg/l	Daphnia magna	OECD 211	
						(Daphnia magna	
						Reproduction Test)	
12.1. Toxicity to algae:	EC50	3d	3,6	mg/l	Selenastrum		
					capricornutum		
12.2. Persistence and	DOC	28d	24	%		OECD 302 B	Not readily
degradability:						(Inherent	biodegradable
						Biodegradability -	
						Zahn-	
						Wellens/EMPA	
						Test)	



Page 9 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.05.2019 / 0008 Replacing version dated / version: 18.10.2018 / 0007 Valid from: 08.05.2019 PDF print date: 10.05.2019 Top Tec ATF 1700 20 L Art.: 3695

12.3. Bioaccumulative	Log Kow	4,5		
potential:				

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and		28d	68	%		OECD 301 D	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Closed Bottle Test)	
12.1. Toxicity to fish:	LC50	96h	2,14	mg/l	Brachydanio rerio	OECD 203 (Fish,	
						Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	21d	1,09	mg/l	Daphnia magna	OECD 211	
						(Daphnia magna	
						Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	0,082	µg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

13 02 06 synthetic engine, gear and lubricating oils

Recommendation:

ആ

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

15 01 02 plastic packaging

15 01 04 metallic packaging

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements	
14.1. UN number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.



Page 10 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.05.2019 / 0008 Replacing version dated / version: 18.10.2018 / 0007 Valid from: 08.05.2019 PDF print date: 10.05.2019 Top Tec ATF 1700 20 L Art.: 3695

Marine Pollutant: 14.5. Environmental hazards:

Transport by air (IATA)

14.2. UN proper shipping name: 14.3. Transport hazard class(es):

14.4. Packing group:

ആ

14.5. Environmental hazards:

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions: Comply with trade association/occupational health regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

2, 3, 8, 11, 12, 15

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H314 Causes severe skin burns and eye damage.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Aquatic Chronic — Hazardous to the aquatic environment - chronic Eye Irrit. - Eye irritation Skin Irrit. — Skin irritation Aquatic Acute - Hazardous to the aquatic environment - acute Acute Tox. — Acute toxicity - oral Skin Corr. — Skin corrosion Eye Dam. - Serious eye damage

Any abbreviations and acronyms used in this document:

n.a Not applicable

Not applicable

n.a.

n.a.



ആ Page 11 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.05.2019 / 0008 Replacing version dated / version: 18.10.2018 / 0007 Valid from: 08.05.2019 PDF print date: 10.05.2019 Top Tec ATF 1700 20 L Art.: 3695 AC **Article Categories** acc., acc. to according, according to ACGIH American Conference of Governmental Industrial Hygienists Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOEL Acceptable Operator Exposure Level AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) ATE BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BAuA BCF Bioconcentration factor BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation) Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BHT BMGV Biological monitoring guidance value (EH40, UK) BOD Biochemical oxygen demand BSEF Bromine Science and Environmental Forum body weight bw Chemical Abstracts Service CAS Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids CEC CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques CIPAC Collaborative International Pesticides Analytical Council CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic COD Chemical oxygen demand CTFA Cosmetic, Toiletry, and Fragrance Association DMEL Derived Minimum Effect Level DNEL Derived No Effect Level Dissolved organic carbon DOC Dwell Time - 50% reduction of start concentration DT50 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes) dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EC European Community ECHA European Chemicals Agency EEA European Economic Area EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances **ELINCS** European List of Notified Chemical Substances EN European Norms EPA United States Environmental Protection Agency (United States of America) ERC **Environmental Release Categories** ES Exposure scenario etc. et cetera European Union FU EWC European Waste Catalogue Fax. Fax number general gen. GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential HET-CAM Hen's Egg Test - Chorionallantoic Membrane HGWP Halocarbon Global Warming Potential IARC International Agency for Research on Cancer International Air Transport Association IATA Intermediate Bulk Container IBC IBC (Code) International Bulk Chemical (Code) IC Inhibitory concentration IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform ChemicaL Information Database LC lethal concentration



ആ Page 12 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.05.2019 / 0008 Replacing version dated / version: 18.10.2018 / 0007 Valid from: 08.05.2019 PDF print date: 10.05.2019 Top Tec ATF 1700 20 L Art.: 3695 LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration Lethal Dose of a chemical I D LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration LOEL Lowest Observed Effect Level LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships n.a. not applicable n.av. not available not checked n.c. n.d.a. no data available NIOSH National Institute of Occupational Safety and Health (United States of America) NOAECNo Observed Adverse Effective Concentration NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level ODP Ozone Depletion Potential OECD Organisation for Economic Co-operation and Development org. organic PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic Chemical product category PC ΡE Polyethylene PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential parts per million ppm PROC Process category PTFE Polytetrafluorethylene REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SADT Self-Accelerating Decomposition Temperature SAR Structure Activity Relationship SU Sector of use SVHC Substances of Very High Concern Tel. Telephone ThOD Theoretical oxygen demand TOC Total organic carbon TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) United Nations Recommendations on the Transport of Dangerous Goods UN RTDG VhF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) VOC Volatile organic compounds vPvB very persistent and very bioaccumulative WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) WEL-TWA, WEL-STEL reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK). World Health Organization WHO wet weight wwt The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.