

GB

Page 1 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 18.07.2019 / 0027
Replacing version dated / version: 09.07.2018 / 0026
Valid from: 18.07.2019
PDF print date: 19.07.2019
Hybrid Additive 250 ml
Art.: 1001

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Hybrid Additive 250 ml
Art.: 1001

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Fuel additive

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany
Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

| Hazard class | Hazard category | Hazard statement |
|--------------|-----------------|--|
| Asp. Tox. | 1 | H304-May be fatal if swallowed and enters airways. |

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H304-May be fatal if swallowed and enters airways.

Page 2 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.07.2019 / 0027
 Replacing version dated / version: 09.07.2018 / 0026
 Valid from: 18.07.2019
 PDF print date: 19.07.2019
 Hybrid Additive 250 ml
 Art.: 1001

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.
 P301+P310+P331-IF SWALLOWED: Immediately call a POISON CENTER / doctor. Do NOT induce vomiting.
 P405-Store locked up.
 P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10, aromatics, >1% naphthalene
 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

When using: development of flammable vapour/air mixture possible.

Product can compose a film on the water surface, which can prevent oxygen exchange.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

| | |
|--|-------------------------------|
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | |
| Registration number (REACH) | 01-2119457273-39-XXXX |
| Index | --- |
| EINECS, ELINCS, NLP | 918-481-9 (REACH-IT List-No.) |
| CAS | --- |
| content % | 80-<100 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Asp. Tox. 1, H304 |

| | |
|--|---|
| Hydrocarbons, C10, aromatics, >1% naphthalene | |
| Registration number (REACH) | --- |
| Index | --- |
| EINECS, ELINCS, NLP | 919-284-0 (REACH-IT List-No.) |
| CAS | (64742-94-5) |
| content % | 1-<2,5 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411 |

| | |
|--|---|
| Naphthalene | Substance for which an EU exposure limit value applies. |
| Registration number (REACH) | --- |
| Index | 601-052-00-2 |
| EINECS, ELINCS, NLP | 202-049-5 |
| CAS | 91-20-3 |
| content % | 0,1-<1 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Carc. 2, H351 Acute Tox. 4, H302 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1) |

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Page 3 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 18.07.2019 / 0027
Replacing version dated / version: 09.07.2018 / 0026
Valid from: 18.07.2019
PDF print date: 19.07.2019
Hybrid Additive 250 ml
Art.: 1001

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.
If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Do not induce vomiting. Consult doctor immediately.
Danger of aspiration.
In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

With long-term contact:

Irritation of the eyes
Headaches
Dizziness
Nausea
Product removes fat.
Drying of the skin.
Dermatitis (skin inflammation)

Ingestion:

Danger of aspiration.
Lung damage
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.
Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂
Dry extinguisher
Foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:
Oxides of carbon
Oxides of nitrogen
Toxic pyrolysis products.
Flammable vapour/air mixtures
Dangerous vapours heavier than air.
In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

Page 4 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 18.07.2019 / 0027
Replacing version dated / version: 09.07.2018 / 0026
Valid from: 18.07.2019
PDF print date: 19.07.2019
Hybrid Additive 250 ml
Art.: 1001

In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.
Avoid inhalation, and contact with eyes or skin.
If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent from entering drainage system.
Prevent surface and ground-water infiltration, as well as ground penetration.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
Keep away from sources of ignition - Do not smoke.
Do not heat to temperatures close to flash point.
Take precautions against electrostatic charges.
Avoid contact with eyes or skin.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
Store product closed and only in original packing.
Not to be stored in gangways or stair wells.
Solvent resistant floor
Do not store with oxidizing agents.
Store in a well ventilated place.
Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
800 mg/m³

Ⓞ

Page 5 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.07.2019 / 0027
 Replacing version dated / version: 09.07.2018 / 0026
 Valid from: 18.07.2019
 PDF print date: 19.07.2019
 Hybrid Additive 250 ml
 Art.: 1001

| Ⓞ | Chemical Name | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | Content %:80- <100 |
|---|--|--|-----------------------|
| | WEL-TWA: 800 mg/m3 | WEL-STEL: --- | --- |
| | Monitoring procedures: | <ul style="list-style-type: none"> - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174) | |
| | BMGV: --- | Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40) | |
| Ⓞ | Chemical Name | Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics | Content %:1-<10 |
| | WEL-TWA: 1200 mg/m3 (>=C7 normal and branched chain alkanes) | WEL-STEL: --- | --- |
| | Monitoring procedures: | <ul style="list-style-type: none"> - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174) | |
| | BMGV: --- | Other information: --- | |
| Ⓞ | Chemical Name | Hydrocarbons, C10, aromatics, >1% naphthalene | Content %:1-<2,5 |
| | WEL-TWA: 500 mg/m3 (Aromatics) | WEL-STEL: --- | --- |
| | Monitoring procedures: | <ul style="list-style-type: none"> - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174) | |
| | BMGV: --- | Other information: --- | |
| Ⓞ | Chemical Name | Naphthalene | Content %:0,1-<1 |
| | WEL-TWA: 500 mg/m3 (Aromatics) (WEL), 10 ppm (50 mg/m3) (EU) | WEL-STEL: --- | --- |
| | Monitoring procedures: | - Compur - KITA-153 U(C) (551 182) | |
| | BMGV: --- | Other information: --- | |

| Naphthalene | | | | | | |
|---------------------|--|-----------------------------|------------|--------|------------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 2,4 | µg/l | |
| | Environment - marine | | PNEC | 0,24 | µg/l | |
| | Environment - sewage treatment plant | | PNEC | 2,9 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 0,0672 | mg/kg dry weight | |
| | Environment - sediment, marine | | PNEC | 0,0672 | mg/kg dry weight | |
| | Environment - soil | | PNEC | 0,0533 | mg/kg dry weight | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 3,57 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 25 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 25 | mg/m3 | |

Ⓞ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 18.07.2019 / 0027
Replacing version dated / version: 09.07.2018 / 0026
Valid from: 18.07.2019
PDF print date: 19.07.2019
Hybrid Additive 250 ml
Art.: 1001

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
Applies only if maximum permissible exposure values are listed here.
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
These are specified by e.g. BS EN 14042.
BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
Solvent resistant protective gloves (EN 374).
If applicable
Suitable are, e.g., safety gloves from KCL GmbH Co., D-36124 Eichenzell, e-mail vertrieb@kcl.de, following specifications:
Protective Viton® / fluoroelastomer gloves (EN 374)
Vitojec 890
Protective nitrile gloves (EN 374).
Minimum layer thickness in mm:
0,4
Permeation time (penetration time) in minutes:
> 480
Protective hand cream recommended.
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
If OES or MEL is exceeded.
Filter A2 P2 (EN 14387), code colour brown, white
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
Not applicable

Additional information on hand protection - No tests have been performed.
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
Selection of materials derived from glove manufacturer's indications.
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.07.2019 / 0027

Replacing version dated / version: 09.07.2018 / 0026

Valid from: 18.07.2019

PDF print date: 19.07.2019

Hybrid Additive 250 ml

Art.: 1001

9.1 Information on basic physical and chemical properties

| | |
|--|--|
| Physical state: | Liquid |
| Colour: | Light yellow |
| Odour: | Characteristic |
| Odour threshold: | Not determined |
| pH-value: | n.a. |
| Melting point/freezing point: | Not determined |
| Initial boiling point and boiling range: | Not determined |
| Flash point: | >63 °C |
| Evaporation rate: | Not determined |
| Flammability (solid, gas): | Not determined |
| Lower explosive limit: | 0,7 Vol-% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics) |
| Upper explosive limit: | 6 Vol-% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics) |
| Vapour pressure: | Not determined |
| Vapour density (air = 1): | Not determined |
| Density: | 0,811 g/ml (15°C) |
| Bulk density: | Not determined |
| Solubility(ies): | Not determined |
| Water solubility: | Insoluble |
| Partition coefficient (n-octanol/water): | Not determined |
| Auto-ignition temperature: | 235-315 °C (Ignition temperature Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics) |
| Decomposition temperature: | Not determined |
| Viscosity: | <7 mm ² /s (40°C) |
| Explosive properties: | Not determined |
| Oxidising properties: | No |

9.2 Other information

| | |
|---------------------------|----------------|
| Miscibility: | Not determined |
| Fat solubility / solvent: | Not determined |
| Conductivity: | Not determined |
| Surface tension: | Not determined |
| Solvents content: | Not determined |

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Hybrid Additive 250 ml

Art.: 1001

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|--------------------------------|----------|-------|------|----------|-------------|--------|
| Acute toxicity, by oral route: | | | | | | n.d.a. |

Page 8 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.07.2019 / 0027
 Replacing version dated / version: 09.07.2018 / 0026
 Valid from: 18.07.2019
 PDF print date: 19.07.2019
 Hybrid Additive 250 ml
 Art.: 1001

| | | | | | | |
|---|--|--|--|--|--|---|
| Acute toxicity, by dermal route: | | | | | | n.d.a. |
| Acute toxicity, by inhalation: | | | | | | n.d.a. |
| Skin corrosion/irritation: | | | | | | n.d.a. |
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin sensitisation: | | | | | | n.d.a. |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | negative, the real Naphthalene content is <1% |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | n.d.a. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | n.d.a. |
| Aspiration hazard: | | | | | | n.d.a. |
| Symptoms: | | | | | | n.d.a. |

| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | | | | |
|--|----------|-------|-----------------------|------------------------|--|---------------------------------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | Analogous conclusion |
| Acute toxicity, by dermal route: | LD50 | >5000 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | Analogous conclusion |
| Acute toxicity, by inhalation: | LC50 | >4951 | mg/m ³ /4h | Rat | OECD 403 (Acute Inhalation Toxicity) | Analogous conclusion, Vapours |
| Skin corrosion/irritation: | | | | | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant, Analogous conclusion |
| Serious eye damage/irritation: | | | | | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant, Analogous conclusion |
| Respiratory or skin sensitisation: | | | | | OECD 406 (Skin Sensitisation) | Not sensitizing, Analogous conclusion |
| Germ cell mutagenicity: | | | | | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative, Analogous conclusion |
| Germ cell mutagenicity: | | | | | OECD 474 (Mammalian Erythrocyte Micronucleus Test) | Negative, Analogous conclusion |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Carcinogenicity: | | | | | OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies) | Negative, Analogous conclusion |
| Reproductive toxicity: | | | | | OECD 414 (Prenatal Developmental Toxicity Study) | Negative, Analogous conclusion |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) | Negative, Analogous conclusion |
| Aspiration hazard: | | | | | | Yes |
| Symptoms: | | | | | | unconsciousness, headaches, dizziness |

GB

Page 9 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.07.2019 / 0027
 Replacing version dated / version: 09.07.2018 / 0026
 Valid from: 18.07.2019
 PDF print date: 19.07.2019
 Hybrid Additive 250 ml
 Art.: 1001

| | | | | | | |
|--------------------|--|--|--|--|--|---|
| Other information: | | | | | | Repeated exposure may cause skin dryness or cracking. |
|--------------------|--|--|--|--|--|---|

| Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | | | | |
|--|----------|-------|-------|------------------------|--|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >5000 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Skin corrosion/irritation: | | | | | | Repeated exposure may cause skin dryness or cracking. |
| Skin corrosion/irritation: | | | | | OECD 404 (Acute Dermal Irritation/Corrosion) | Analogous conclusion, Drying of the skin., Dermatitis (skin inflammation) |
| Serious eye damage/irritation: | | | | | OECD 405 (Acute Eye Irritation/Corrosion) | Analogous conclusion, Slightly irritant |
| Respiratory or skin sensitisation: | | | | Rat | | Not sensitising |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | in vivo | Negative |
| Carcinogenicity: | | | | | OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies) | Analogous conclusion, Negative |
| Reproductive toxicity: | | | | | OECD 414 (Prenatal Developmental Toxicity Study) | Analogous conclusion, Negative |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | Analogous conclusion, No indications of such an effect. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) | Analogous conclusion, Not to be expected |
| Aspiration hazard: | | | | | | Yes |
| Symptoms: | | | | | | drying of the skin., headaches, fatigue, dizziness, nausea, diarrhoea, vomiting |

| Hydrocarbons, C10, aromatics, >1% naphthalene | | | | | | |
|---|----------|-------|-------|----------|--------------------------------------|-------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | ~7093 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >2000 | mg/kg | Rat | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | >4688 | mg/m3 | Rat | OECD 403 (Acute Inhalation Toxicity) | |

Page 10 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.07.2019 / 0027
 Replacing version dated / version: 09.07.2018 / 0026
 Valid from: 18.07.2019
 PDF print date: 19.07.2019
 Hybrid Additive 250 ml
 Art.: 1001

| | | | | | | |
|------------------------------------|--|--|--|------------|-------------------------------|-----------------|
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | Not sensitizing |
|------------------------------------|--|--|--|------------|-------------------------------|-----------------|

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

| Hybrid Additive 250 ml Art.: 1001 | | | | | | | |
|--|----------|------|-------|------|----------|-------------|--|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | | | | | | | n.d.a. |
| 12.1. Toxicity to daphnia: | | | | | | | n.d.a. |
| 12.1. Toxicity to algae: | | | | | | | n.d.a. |
| 12.2. Persistence and degradability: | | | | | | | Isolate as much as possible with an oil separator. n.d.a. |
| 12.3. Bioaccumulative potential: | | | | | | | n.d.a. |
| 12.4. Mobility in soil: | | | | | | | n.d.a. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | n.d.a. |
| 12.6. Other adverse effects: | | | | | | | n.d.a. |
| Other information: | | | | | | | According to the recipe, contains no AOX. |

| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | | | | | |
|--|----------|------|-------|------|---------------------------------|--|--------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Water solubility: | | | | | | | Product floats on the water surface. |
| 12.1. Toxicity to fish: | LL50 | 96h | >1000 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to fish: | NOELR | 28d | 0,101 | mg/l | Oncorhynchus mykiss | | |
| 12.1. Toxicity to daphnia: | EL50 | 48h | >1000 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to daphnia: | NOELR | 21d | 0,176 | mg/l | Daphnia magna | | |
| 12.2. Persistence and degradability: | | 28d | 80 | % | Daphnia magna activated sludge | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) | Readily biodegradable |
| 12.1. Toxicity to algae: | EL50 | 72h | >1000 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| Other organisms: | EL50 | 48h | >1000 | mg/l | Tetrahymena pyriformis | | |

| Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | | | | | |
|--|----------|------|-------|------|---------------------|-------------|-------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | NOELR | 28d | 0,17 | mg/l | Oncorhynchus mykiss | QSAR | |
| 12.1. Toxicity to daphnia: | NOELR | 21d | 1,22 | mg/l | Daphnia magna | QSAR | |

Page 11 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.07.2019 / 0027
 Replacing version dated / version: 09.07.2018 / 0026
 Valid from: 18.07.2019
 PDF print date: 19.07.2019
 Hybrid Additive 250 ml
 Art.: 1001

| | | | | | | | |
|---|---------|-----|------|------|-------------------------------------|--|---|
| 12.1. Toxicity to algae: | NOELR | 72h | 1000 | mg/l | Pseudokirchneriell a subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | 28d | 69 | % | | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) | Readily biodegradable |
| 12.3. Bioaccumulative potential: | Log Pow | | 6-8 | | | | High |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

Hydrocarbons, C10, aromatics, >1% naphthalene

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|----------------------------|----------|------|-------|------|-----------------------------|--|-------|
| 12.1. Toxicity to daphnia: | EL50 | 48h | 10 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | EL50 | 72h | >1-<3 | mg/l | Raphidocelis subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.
EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 07 04 other organic solvents, washing liquids and mother liquors

14 06 03 other solvents and solvent mixtures

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Untampered packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 18.07.2019 / 0027

Replacing version dated / version: 09.07.2018 / 0026

Valid from: 18.07.2019

PDF print date: 19.07.2019

Hybrid Additive 250 ml

Art.: 1001

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

n.a.

14.4. Packing group:

n.a.

Marine Pollutant:

n.a.

14.5. Environmental hazards:

Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

n.a.

14.4. Packing group:

n.a.

14.5. Environmental hazards:

Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

95,3 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

2

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

| Classification in accordance with regulation (EC) No. 1272/2008 (CLP) | Evaluation method used |
|---|--|
| Asp. Tox. 1, H304 | Classification according to calculation procedure. |

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Asp. Tox. — Aspiration hazard

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Carc. — Carcinogenicity

Acute Tox. — Acute toxicity - oral

Aquatic Acute — Hazardous to the aquatic environment - acute

Page 13 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 18.07.2019 / 0027
 Replacing version dated / version: 09.07.2018 / 0026
 Valid from: 18.07.2019
 PDF print date: 19.07.2019
 Hybrid Additive 250 ml
 Art.: 1001

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BSEF The International Bromine Council
 bw body weight
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 OECD Organisation for Economic Co-operation and Development
 org. organic
 PBT persistent, bioaccumulative and toxic
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 ppm parts per million
 PVC Polyvinylchloride
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SVHC Substances of Very High Concern

Page 14 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 18.07.2019 / 0027
Replacing version dated / version: 09.07.2018 / 0026
Valid from: 18.07.2019
PDF print date: 19.07.2019
Hybrid Additive 250 ml
Art.: 1001

Tel. Telephone
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.