

Page 1 of 18
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 22.02.2019 / 0012
Replacing version dated / version: 17.10.2018 / 0011
Valid from: 22.02.2019
PDF print date: 09.03.2019
Oel-Fleck-Entferner 400 mL
Art.: 3315

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Oel-Fleck-Entferner 400 mL
Art.: 3315

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Solvent

Cleaner

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC35 - Washing and cleaning products

Process category [PROC]:

PROC 7 - Industrial spraying

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC11 - Non industrial spraying

PROC19 - Manual activities involving hand contact

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 2 - Formulation into mixture

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 5 - Use at industrial site leading to inclusion into/onto article

ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC 8c - Widespread use leading to inclusion into/onto article (indoor)

ERC 8d - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

ERC 8f - Widespread use leading to inclusion into/onto article (outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany
Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 17.10.2018 / 0011

Valid from: 22.02.2019

PDF print date: 09.03.2019

Oel-Fleck-Entferner 400 mL

Art.: 3315

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Irrit.	2	H315-Causes skin irritation.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H319-Causes serious eye irritation. H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P280-Wear protective gloves and eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

Without adequate ventilation, formation of explosive mixtures may be possible.

Propan-2-ol

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Danger of bursting (explosion) when heated

When using: development of explosive vapour/air mixture possible.

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a.

3.2 Mixture

Propan-2-ol	
Registration number (REACH)	---
Index	603-117-00-0

Page 3 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2019 / 0012
 Replacing version dated / version: 17.10.2018 / 0011
 Valid from: 22.02.2019
 PDF print date: 09.03.2019
 Oel-Fleck-Entferner 400 mL
 Art.: 3315

EINECS, ELINCS, NLP	200-661-7
CAS	67-63-0
content %	40-60
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Xylene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	601-022-00-9
EINECS, ELINCS, NLP	215-535-7
CAS	1330-20-7
content %	10-<12,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 Acute Tox. 4, H332 Acute Tox. 4, H312 Skin Irrit. 2, H315

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the respiratory tract

Coughing

Headaches

Nausea

Effects/damages the central nervous system

Narcotic effect.

With long-term contact:

Dermatitis (skin inflammation)

Irritation of the skin.

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 22.02.2019 / 0012
Replacing version dated / version: 17.10.2018 / 0011
Valid from: 22.02.2019
PDF print date: 09.03.2019
Oel-Fleck-Entferner 400 mL
Art.: 3315

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO₂ / dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Explosive vapour/air or gas/air mixtures.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

Toxic gases

Danger of bursting (explosion) when heated

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Do not use the product in enclosed spaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2019 / 0012
 Replacing version dated / version: 17.10.2018 / 0011
 Valid from: 22.02.2019
 PDF print date: 09.03.2019
 Oel-Fleck-Entferner 400 mL
 Art.: 3315

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Do not store with oxidizing agents.
 Observe special regulations for aerosols!
 Observe special storage conditions.
 Keep protected from direct sunlight and temperatures over 50°C.
 Store in a well ventilated place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Propan-2-ol		Content %:40-60
WEL-TWA: 400 ppm (999 mg/m3)	WEL-STEL: 500 ppm (1250 mg/m3)	---	
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-122 SA(C) (549 277) - Compur - KITA-150 U (550 382) - Draeger - Alcohol 25/a i-Propanol (81 01 631) - DFG (D) (Loesungsmittelgemische), DFG (E) (Solvent mixtures 6) - 1998, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 66-3 (2004) - Draeger - Alcohol 100/a (CH 29 701) 		
BMGV: ---	Other information: ---		
Chemical Name	Xylene		Content %:10- <12,5
WEL-TWA: 50 ppm (220 mg/m3) (WEL), 50 ppm (221 mg/m3) (EU)	WEL-STEL: 100 ppm (441 mg/m3 (WEL), 100 ppm (442 mg/m3) (EU)		---
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-143 SA (550 325) - Compur - KITA-143 SB (505 998) - Draeger - Xylene 10/a (67 33 161) - MTA/MA-030/A92 (Determination of aromatic hydrocarbons (benzene, toluene, ethylbenzene, p-xylene, 1,2,4-trimethylbenzene) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 47-1 (2004) 		
BMGV: 650 mmol methyl hippuric acid/mol creatinine in urine, post shift (Xylene, o-, m-, p- or mixed isomers) (BMGV)	Other information: Sk (WEL)		
Chemical Name	Butane		Content %:
WEL-TWA: 600 ppm (1450 mg/m3)	WEL-STEL: 750 ppm (1810 mg/m3)	---	
Monitoring procedures:	- Compur - KITA-221 SA (549 459)		
BMGV: ---	Other information: ---		
Chemical Name	Propane		Content %:
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---	
Monitoring procedures:	- Compur - KITA-125 SA (549 954)		
BMGV: ---	Other information: ---		
Chemical Name	Isobutane		Content %:
WEL-TWA: 1000 ppm (EX) (ACGIH)	WEL-STEL: ---	---	
Monitoring procedures:	- Compur - KITA-113 SB(C) (549 368)		
BMGV: ---	Other information: ---		
Chemical Name	Silicon dioxide - amorphous		Content %:
WEL-TWA: 6 mg/m3 (total inh. dust), 2,4 mg/m3 (resp. dust)	WEL-STEL: ---	---	
Monitoring procedures:	---		
BMGV: ---	Other information: ---		
Chemical Name	Paraffin wax, fume		Content %:
WEL-TWA: 2 mg/m3	WEL-STEL: 6 mg/m3	---	
Monitoring procedures:	---		

Page 6 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2019 / 0012
 Replacing version dated / version: 17.10.2018 / 0011
 Valid from: 22.02.2019
 PDF print date: 09.03.2019
 Oel-Fleck-Entferner 400 mL
 Art.: 3315

BMGV: ---

Other information: ---

Propan-2-ol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	140,9	mg/l	
	Environment - marine		PNEC	140,9	mg/l	
	Environment - sediment, freshwater		PNEC	552	mg/kg	
	Environment - sediment, marine		PNEC	552	mg/kg	
	Environment - soil		PNEC	28	mg/kg	
	Environment - sewage treatment plant		PNEC	2251	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	140,9	mg/l	
Consumer	Human - dermal	Long term	DNEL	319	mg/kg	(1 d)
Consumer	Human - inhalation	Long term	DNEL	89	mg/m ³	
Consumer	Human - oral	Long term	DNEL	26	mg/kg	(1 d)
Workers / employees	Human - dermal	Long term	DNEL	888	mg/kg	(1 d)
Workers / employees	Human - inhalation	Long term	DNEL	500	mg/m ³	

Xylene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,327	mg/l	
	Environment - sediment, freshwater		PNEC	12,46	mg/kg	
	Environment - soil		PNEC	2,31	mg/kg	
	Environment - marine		PNEC	0,327	mg/l	
	Environment - sediment, marine		PNEC	12,46	mg/kg	
	Environment - sewage treatment plant		PNEC	6,58	mg/l	
Consumer	Human - inhalation	Short term, local effects	DNEL	174	mg/m ³	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	174	mg/m ³	
Consumer	Human - dermal	Long term, systemic effects	DNEL	108	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	14,8	mg/m ³	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	289	mg/m ³	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	289	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	77	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	180	mg/kg	

Silicon dioxide - amorphous						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4	mg/m ³	

Page 7 of 18
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 22.02.2019 / 0012
Replacing version dated / version: 17.10.2018 / 0011
Valid from: 22.02.2019
PDF print date: 09.03.2019
Oel-Fleck-Entferner 400 mL
Art.: 3315

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

$\geq 0,35$

Permeation time (penetration time) in minutes:

≤ 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

Page 8 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2019 / 0012
 Replacing version dated / version: 17.10.2018 / 0011
 Valid from: 22.02.2019
 PDF print date: 09.03.2019
 Oel-Fleck-Entferner 400 mL
 Art.: 3315

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	n.a.
Flash point:	n.a.
Evaporation rate:	n.a.
Flammability (solid, gas):	n.a.
Lower explosive limit:	1,1 Vol-%
Upper explosive limit:	12 Vol-%
Vapour pressure:	3400 hPa (20°C)
Vapour density (air = 1):	Vapours heavier than air.
Density:	0,75 g/ml (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	365 °C (Ignition temperature)
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive. When using: development of explosive vapour/air mixture possible.
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

See also section 7.

Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

Page 9 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2019 / 0012
 Replacing version dated / version: 17.10.2018 / 0011
 Valid from: 22.02.2019
 PDF print date: 09.03.2019
 Oel-Fleck-Entferner 400 mL
 Art.: 3315

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Oel-Fleck-Entferner 400 mL

Art.: 3315

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Propan-2-ol

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4570-5840	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	13900	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	30	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Specific target organ toxicity - repeated exposure (STOT-RE):						Target organ(s): liver
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, vomiting, headaches, fatigue, dizziness, nausea

Page 10 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2019 / 0012
 Replacing version dated / version: 17.10.2018 / 0011
 Valid from: 22.02.2019
 PDF print date: 09.03.2019
 Oel-Fleck-Entferner 400 mL
 Art.: 3315

Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
---	-------	-----	-------	-----	--	--

Xylene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2840	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>1700	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	21,7	mg/l/4h	Rat		Vapours, Does not conform with EU classification.
Skin corrosion/irritation:				Rabbit		Irritant
Serious eye damage/irritation:				Rabbit		Slightly irritant
Respiratory or skin sensitisation:					(Patch-Test)	Negative
Symptoms:						breathing difficulties, drying of the skin., drowsiness, unconsciousness , burning of the membranes of the nose and throat, vomiting, skin afflictions, heart/circulatory disorders, coughing, headaches, drowsiness, dizziness, nausea

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness , frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative

Page 12 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2019 / 0012
 Replacing version dated / version: 17.10.2018 / 0011
 Valid from: 22.02.2019
 PDF print date: 09.03.2019
 Oel-Fleck-Entferner 400 mL
 Art.: 3315

12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							Product is slightly volatile.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

Propan-2-ol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Leuciscus idus		
12.1. Toxicity to daphnia:	EC50	48h	2285	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:		21d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:			99,9	%		OECD 303 A (Simulation Test - Aerobic Sewage Treatment - Activated Sludge Units)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0,05			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.4. Mobility in soil:	Koc		1,1				Expert judgement
Toxicity to bacteria:	EC50		>1000	mg/l	activated sludge		
Other information:	ThOD		2,4	g/g			
Other information:	BOD5		53	%			
Other information:	COD		96	%			References
Other information:	COD		2,4	g/g			
Other information:	BOD		1171	mg/g			

Xylene

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	86	mg/l	Leuciscus idus		
12.1. Toxicity to fish:	LC50	96h	8,2	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	24h	75,5	mg/l	Daphnia magna		
12.1. Toxicity to algae:	IC50	72h	10	mg/l			
12.2. Persistence and degradability:							Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		>3				
12.3. Bioaccumulative potential:	BCF		0,6-15				

Page 13 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2019 / 0012
 Replacing version dated / version: 17.10.2018 / 0011
 Valid from: 22.02.2019
 PDF print date: 09.03.2019
 Oel-Fleck-Entferner 400 mL
 Art.: 3315

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and degradability:							Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Silicon dioxide - amorphous							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.1. Toxicity to algae:	IC50	72h	440	mg/l	Pseudokirchneriella subcapitata	IUCLID Chem. Data Sheet (ESIS)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	60	mg/l	Pseudokirchneriella subcapitata	IUCLID Chem. Data Sheet (ESIS)	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Page 14 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2019 / 0012
 Replacing version dated / version: 17.10.2018 / 0011
 Valid from: 22.02.2019
 PDF print date: 09.03.2019
 Oel-Fleck-Entferner 400 mL
 Art.: 3315

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)
 16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.
 Pay attention to local and national official regulations.
 Take full aerosol cans to problem waste collection.
 Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.
 15 01 04 metallic packaging
 15 01 10 packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

General statements

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

Classification code:

5F

LQ:

1 L

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

D



Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

EmS:

F-D, S-U

Marine Pollutant:

n.a

14.5. Environmental hazards:

Not applicable



Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

14.5. Environmental hazards:

Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Page 15 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2019 / 0012
 Replacing version dated / version: 17.10.2018 / 0011
 Valid from: 22.02.2019
 PDF print date: 09.03.2019
 Oel-Fleck-Entferner 400 mL
 Art.: 3315

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

~ 89,4 %

REGULATION (EC) No 648/2004

30 % and more
 aliphatic hydrocarbons
 5 % or over but less than 15 %
 aromatic hydrocarbons

perfumes
 LIMONENE

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

2, 3, 8, 11, 12, 16

Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

Page 16 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2019 / 0012
 Replacing version dated / version: 17.10.2018 / 0011
 Valid from: 22.02.2019
 PDF print date: 09.03.2019
 Oel-Fleck-Entferner 400 mL
 Art.: 3315

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H336 May cause drowsiness or dizziness.

Eye Irrit. — Eye irritation
 Skin Irrit. — Skin irritation
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects
 Aerosol — Aerosols
 Flam. Liq. — Flammable liquid
 Acute Tox. — Acute toxicity - inhalation
 Acute Tox. — Acute toxicity - dermal

Any abbreviations and acronyms used in this document:

AC Article Categories
 acc., acc. to according, according to
 ACGIH American Conference of Governmental Industrial Hygienists
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOEL Acceptable Operator Exposure Level
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
 BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
 BMGV Biological monitoring guidance value (EH40, UK)
 BOD Biochemical oxygen demand
 BSEF Bromine Science and Environmental Forum
 bw body weight
 CAS Chemical Abstracts Service
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
 CIPAC Collaborative International Pesticides Analytical Council
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 COD Chemical oxygen demand
 CTFA Cosmetic, Toiletry, and Fragrance Association
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 DT50 Dwell Time - 50% reduction of start concentration
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEA European Economic Area
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms

Page 17 of 18
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.02.2019 / 0012
 Replacing version dated / version: 17.10.2018 / 0011
 Valid from: 22.02.2019
 PDF print date: 09.03.2019
 Oel-Fleck-Entferner 400 mL
 Art.: 3315

EPA United States Environmental Protection Agency (United States of America)
 ERC Environmental Release Categories
 ES Exposure scenario
 etc. et cetera
 EU European Union
 EWC European Waste Catalogue
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane
 HGWP Halocarbon Global Warming Potential
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC Intermediate Bulk Container
 IBC (Code) International Bulk Chemical (Code)
 IC Inhibitory concentration
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 LC lethal concentration
 LC50 lethal concentration 50 percent kill
 LCLo lowest published lethal concentration
 LD Lethal Dose of a chemical
 LD50 Lethal Dose, 50% kill
 LDLo Lethal Dose Low
 LOAEL Lowest Observed Adverse Effect Level
 LOEC Lowest Observed Effect Concentration
 LOEL Lowest Observed Effect Level
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute of Occupational Safety and Health (United States of America)
 NOAEC No Observed Adverse Effective Concentration
 NOAEL No Observed Adverse Effect Level
 NOEC No Observed Effect Concentration
 NOEL No Observed Effect Level
 ODP Ozone Depletion Potential
 OECD Organisation for Economic Co-operation and Development
 org. organic
 PAH polycyclic aromatic hydrocarbon
 PBT persistent, bioaccumulative and toxic
 PC Chemical product category
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 POCP Photochemical ozone creation potential
 ppm parts per million
 PROC Process category
 PTFE Polytetrafluorethylene
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SADT Self-Accelerating Decomposition Temperature
 SAR Structure Activity Relationship
 SU Sector of use
 SVHC Substances of Very High Concern
 Tel. Telephone

Page 18 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 22.02.2019 / 0012

Replacing version dated / version: 17.10.2018 / 0011

Valid from: 22.02.2019

PDF print date: 09.03.2019

Oel-Fleck-Entferner 400 mL

Art.: 3315

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.