

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Epoxy-Kleber 25 mL**  
**Art.: 6183 (A)**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

Resin  
Adhesive

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany  
Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

##### Emergency information services / official advisory body:

---

##### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.02.2019 / 0012  
 Replacing version dated / version: 30.08.2018 / 0011  
 Valid from: 22.02.2019  
 PDF print date: 09.03.2019  
 Epoxy-Kleber 25 mL  
 Art.: 6183 (A)



### Warning

H319-Causes serious eye irritation. H315-Causes skin irritation. H317-May cause an allergic skin reaction. H411-Toxic to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves / eye protection / face protection.

P302+P352-IF ON SKIN: Wash with plenty of water / soap. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P314-Get medical advice / attention if you feel unwell.

P501-Dispose of contents / container to an approved waste disposal facility.

Reaction product: bisphenol-A-(epichlorhydrin)

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Contains epoxy constituents. Avoid skin contact. Protective gloves should be worn.

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

<b>Reaction product: bisphenol-A-(epichlorhydrin)</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	603-074-00-8
<b>EINECS, ELINCS, NLP</b>	500-033-5 (NLP)
<b>CAS</b>	25068-38-6
<b>content %</b>	80-<100
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Page 3 of 12  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 22.02.2019 / 0012  
Replacing version dated / version: 30.08.2018 / 0011  
Valid from: 22.02.2019  
PDF print date: 09.03.2019  
Epoxy-Kleber 25 mL  
Art.: 6183 (A)

Never pour anything into the mouth of an unconscious person!

### **Inhalation**

Remove person from danger area.  
Supply person with fresh air and consult doctor according to symptoms.

### **Skin contact**

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

### **Eye contact**

Remove contact lenses.  
Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

### **Ingestion**

Rinse the mouth thoroughly with water.  
Do not induce vomiting - give copious water to drink. Consult doctor immediately.

## **4.2 Most important symptoms and effects, both acute and delayed**

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.  
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

## **4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

## **SECTION 5: Firefighting measures**

### **5.1 Extinguishing media**

#### **Suitable extinguishing media**

Water jet spray  
CO<sub>2</sub>  
Foam  
Extinction powder

#### **Unsuitable extinguishing media**

High volume water jet

### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon  
Hydrogen chloride  
Toxic gases

### **5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary.  
Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure sufficient supply of air.  
Avoid contact with eyes or skin.  
If applicable, caution - risk of slipping.

### **6.2 Environmental precautions**

If leakage occurs, dam up.  
Resolve leaks if this possible without risk.  
Prevent from entering drainage system.  
Prevent surface and ground-water infiltration, as well as ground penetration.  
If accidental entry into drainage system occurs, inform responsible authorities.

### **6.3 Methods and material for containment and cleaning up**

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

Page 4 of 12  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.02.2019 / 0012  
 Replacing version dated / version: 30.08.2018 / 0011  
 Valid from: 22.02.2019  
 PDF print date: 09.03.2019  
 Epoxy-Kleber 25 mL  
 Art.: 6183 (A)

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
 Avoid contact with eyes or skin.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
 Not to be stored in gangways or stair wells.  
 Store product closed and only in original packing.  
 Do not store with oxidizing agents.  
 Do not store with acids.  
 Protect from direct sunlight and warming.  
 Store in a well ventilated place.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Reaction product: bisphenol-A-(epichlorhydrin)						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,003	mg/l	
	Environment - marine		PNEC	0,0003	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,018	mg/l	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - sediment, freshwater		PNEC	0,5	mg/kg dw	
	Environment - sediment, marine		PNEC	0,5	mg/kg dw	
	Environment - soil		PNEC	0,05	mg/kg dw	
	Environment - oral (animal feed)		PNEC	11	mg/kg	
Consumer	Human - dermal	Short term, systemic effects	DNEL	3,571	mg/kg bw/day	
Consumer	Human - oral	Short term, systemic effects	DNEL	0,75	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,75	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,75	mg/m <sup>3</sup>	

Page 5 of 12  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.02.2019 / 0012  
 Replacing version dated / version: 30.08.2018 / 0011  
 Valid from: 22.02.2019  
 PDF print date: 09.03.2019  
 Epoxy-Kleber 25 mL  
 Art.: 6183 (A)

Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,75	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	3,6	mg/kg bw/day	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	8,33	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	12,25	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	8,3	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	12,3	mg/m <sup>3</sup>	

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Chemical resistant protective gloves (EN 374).  
 Recommended  
 With short-term contact:  
 Protective gloves in butyl rubber (EN 374).  
 Minimum layer thickness in mm:  
 > 0,4  
 Permeation time (penetration time) in minutes:  
 > 120  
 With long-term contact:  
 Protective gloves in butyl rubber (EN 374).  
 Minimum layer thickness in mm:  
 > 0,4  
 Permeation time (penetration time) in minutes:  
 > 480  
 Protective hand cream recommended.  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
 Normally not necessary.  
 If fumes build up, use suitable breathing mask.  
 Filter A2 P2 (EN 14387), code colour brown, white  
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.

Page 6 of 12  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.02.2019 / 0012  
 Replacing version dated / version: 30.08.2018 / 0011  
 Valid from: 22.02.2019  
 PDF print date: 09.03.2019  
 Epoxy-Kleber 25 mL  
 Art.: 6183 (A)

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Viscous
Colour:	Colourless
Odour:	Mild
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	>250 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1,1-1,17 g/ml
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	>300 °C
Viscosity:	8000-16000 mPas (25°C, RV Spindel 6 (50 rpm) )
Explosive properties:	Not determined
Oxidising properties:	Not determined

### 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

Strong heat

### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids.

Avoid contact with strong alkalis.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.02.2019 / 0012  
 Replacing version dated / version: 30.08.2018 / 0011  
 Valid from: 22.02.2019  
 PDF print date: 09.03.2019  
 Epoxy-Kleber 25 mL  
 Art.: 6183 (A)

## 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

#### Epoxy-Kleber 25 mL

##### Art.: 6183 (A)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

#### Reaction product: bisphenol-A-(epichlorhydrin)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Sensitising (skin contact)
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Sensitising (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Positive
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOEL	540	mg/kg		OECD 416 (Two-generation Reproduction Toxicity Study)	
Reproductive toxicity:				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	50	mg/kg bw/d			
Aspiration hazard:						No diarrhoea, weight loss
Symptoms:						

Page 8 of 12  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.02.2019 / 0012  
 Replacing version dated / version: 30.08.2018 / 0011  
 Valid from: 22.02.2019  
 PDF print date: 09.03.2019  
 Epoxy-Kleber 25 mL  
 Art.: 6183 (A)

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

### Epoxy-Kleber 25 mL

#### Art.: 6183 (A)

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

### Reaction product: bisphenol-A-(epichlorhydrin)

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	1,2	mg/l	Oncorhynchus mykiss	U.S. EPA ECOTOX Database	
12.1. Toxicity to daphnia:	EC50	48h	1,1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,3	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	9,4	mg/l	Selenastrum capricornutum	U.S. EPA ECOTOX Database	
12.1. Toxicity to fish:	LC50	96h	2	mg/l	Leuciscus idus		
12.2. Persistence and degradability:		28d	5	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		3,8				
12.1. Toxicity to algae:	EC50	96h	220	mg/l	Scenedesmus subspicatus		
Other information:							Contains organically bound halogens, which may contribute to the AOX value in wastewater.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods



Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.02.2019 / 0012  
 Replacing version dated / version: 30.08.2018 / 0011  
 Valid from: 22.02.2019  
 PDF print date: 09.03.2019  
 Epoxy-Kleber 25 mL  
 Art.: 6183 (A)

## For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

## For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

15 01 02 plastic packaging

15 01 04 metallic packaging

## SECTION 14: Transport information

### General statements

14.1. UN number: 3082

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Classification code:

M6

LQ:

5 L

14.5. Environmental hazards:

environmentally hazardous

Tunnel restriction code:

-



### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

EmS:

F-A, S-F

Marine Pollutant:

Yes

14.5. Environmental hazards:

environmentally hazardous



### Transport by air (IATA)

14.2. UN proper shipping name:

Environmentally hazardous substance, liquid, n.o.s. (EPOXY RESIN)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

14.5. Environmental hazards:

environmentally hazardous



### 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

GB

Page 10 of 12  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.02.2019 / 0012  
 Replacing version dated / version: 30.08.2018 / 0011  
 Valid from: 22.02.2019  
 PDF print date: 09.03.2019  
 Epoxy-Kleber 25 mL  
 Art.: 6183 (A)

Observe restrictions:  
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!  
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

### REGULATION (EC) No 648/2004

n.a.

Observe incident regulations.

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 2, 3, 8, 11, 12, 16  
 Employee training in handling dangerous goods is required.  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H411 Toxic to aquatic life with long lasting effects.

Eye Irrit. — Eye irritation  
 Skin Irrit. — Skin irritation  
 Skin Sens. — Skin sensitization  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic

### Any abbreviations and acronyms used in this document:

AC Article Categories  
 acc., acc. to according, according to

Page 11 of 12  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.02.2019 / 0012  
 Replacing version dated / version: 30.08.2018 / 0011  
 Valid from: 22.02.2019  
 PDF print date: 09.03.2019  
 Epoxy-Kleber 25 mL  
 Art.: 6183 (A)

ACGIH American Conference of Governmental Industrial Hygienists  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOEL Acceptable Operator Exposure Level  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)  
 BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)  
 BMGV Biological monitoring guidance value (EH40, UK)  
 BOD Biochemical oxygen demand  
 BSEF Bromine Science and Environmental Forum  
 bw body weight  
 CAS Chemical Abstracts Service  
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids  
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques  
 CIPAC Collaborative International Pesticides Analytical Council  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 COD Chemical oxygen demand  
 CTFA Cosmetic, Toiletry, and Fragrance Association  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 DOC Dissolved organic carbon  
 DT50 Dwell Time - 50% reduction of start concentration  
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EC European Community  
 ECHA European Chemicals Agency  
 EEA European Economic Area  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ERC Environmental Release Categories  
 ES Exposure scenario  
 etc. et cetera  
 EU European Union  
 EWC European Waste Catalogue  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane  
 HGWP Halocarbon Global Warming Potential  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC Intermediate Bulk Container  
 IBC (Code) International Bulk Chemical (Code)  
 IC Inhibitory concentration  
 IMDG-code International Maritime Code for Dangerous Goods  
 incl. including, inclusive  
 IUCLID International Uniform Chemical Information Database  
 LC lethal concentration  
 LC50 lethal concentration 50 percent kill  
 LCLo lowest published lethal concentration

Page 12 of 12  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 22.02.2019 / 0012  
 Replacing version dated / version: 30.08.2018 / 0011  
 Valid from: 22.02.2019  
 PDF print date: 09.03.2019  
 Epoxy-Kleber 25 mL  
 Art.: 6183 (A)

LD Lethal Dose of a chemical  
 LD50 Lethal Dose, 50% kill  
 LDLo Lethal Dose Low  
 LOAEL Lowest Observed Adverse Effect Level  
 LOEC Lowest Observed Effect Concentration  
 LOEL Lowest Observed Effect Level  
 LQ Limited Quantities  
 MARPOL International Convention for the Prevention of Marine Pollution from Ships  
 n.a. not applicable  
 n.av. not available  
 n.c. not checked  
 n.d.a. no data available  
 NIOSH National Institute of Occupational Safety and Health (United States of America)  
 NOAEC No Observed Adverse Effective Concentration  
 NOAEL No Observed Adverse Effect Level  
 NOEC No Observed Effect Concentration  
 NOEL No Observed Effect Level  
 ODP Ozone Depletion Potential  
 OECD Organisation for Economic Co-operation and Development  
 org. organic  
 PAH polycyclic aromatic hydrocarbon  
 PBT persistent, bioaccumulative and toxic  
 PC Chemical product category  
 PE Polyethylene  
 PNEC Predicted No Effect Concentration  
 POCP Photochemical ozone creation potential  
 ppm parts per million  
 PROC Process category  
 PTFE Polytetrafluorethylene  
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
 SADT Self-Accelerating Decomposition Temperature  
 SAR Structure Activity Relationship  
 SU Sector of use  
 SVHC Substances of Very High Concern  
 Tel. Telephone  
 ThOD Theoretical oxygen demand  
 TOC Total organic carbon  
 TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)  
 UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
 VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))  
 VOC Volatile organic compounds  
 vPvB very persistent and very bioaccumulative  
 WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).  
 WHO World Health Organization  
 wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
 No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.

GB

Page 1 of 10  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 11.03.2019 / 0011  
Replacing version dated / version: 30.08.2018 / 0010  
Valid from: 11.03.2019  
PDF print date: 11.03.2019  
Epoxy-Kleber 25 mL  
Art.: 6183 (B)

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Epoxy-Kleber 25 mL**  
**Art.: 6183 (B)**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Adhesive  
Hardener

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany  
Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
Skin Sens.	1	H317-May cause an allergic skin reaction.

#### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**



Warning

Page 2 of 10  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.03.2019 / 0011  
 Replacing version dated / version: 30.08.2018 / 0010  
 Valid from: 11.03.2019  
 PDF print date: 11.03.2019  
 Epoxy-Kleber 25 mL  
 Art.: 6183 (B)

H317-May cause an allergic skin reaction.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.  
 P280-Wear protective gloves.  
 P302+P352-IF ON SKIN: Wash with plenty of water / soap. P333+P313-If skin irritation or rash occurs: Get medical advice / attention.  
 P501-Dispose of contents / container to an approved waste disposal facility.

3-trimethoxysilylpropane-1-thiol

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

3-trimethoxysilylpropane-1-thiol	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	224-588-5
CAS	4420-74-0
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302 Skin Sens. 1, H317 Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2019 / 0011

Replacing version dated / version: 30.08.2018 / 0010

Valid from: 11.03.2019

PDF print date: 11.03.2019

Epoxy-Kleber 25 mL

Art.: 6183 (B)

#### **4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

### **SECTION 5: Firefighting measures**

#### **5.1 Extinguishing media**

##### **Suitable extinguishing media**

CO<sub>2</sub>

Water jet spray

Dry extinguisher

Alcohol resistant foam

##### **Unsuitable extinguishing media**

High volume water jet

#### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon

Oxides of sulphur

Hydrogen sulphide

Toxic gases

#### **5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

### **SECTION 6: Accidental release measures**

#### **6.1 Personal precautions, protective equipment and emergency procedures**

Keep unprotected persons away.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

#### **6.2 Environmental precautions**

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

#### **6.3 Methods and material for containment and cleaning up**

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

#### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### **7.1 Precautions for safe handling**

##### **7.1.1 General recommendations**

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

##### **7.1.2 Notes on general hygiene measures at the workplace**



Page 4 of 10  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 11.03.2019 / 0011  
Replacing version dated / version: 30.08.2018 / 0010  
Valid from: 11.03.2019  
PDF print date: 11.03.2019  
Epoxy-Kleber 25 mL  
Art.: 6183 (B)

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
Not to be stored in gangways or stair wells.  
Store product closed and only in original packing.  
Do not store with oxidizing agents.  
Do not store with acids.  
Protect from direct sunlight and warming.  
Store in a well ventilated place.  
Store in a dry place.

## 7.3 Specific end use(s)

No information available at present.

# SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

---

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
Applies only if maximum permissible exposure values are listed here.

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
Chemical resistant protective gloves (EN 374).

Recommended

With short-term contact:

Protective gloves in butyl rubber (EN 374).

Minimum layer thickness in mm:

> 0,7

Permeation time (penetration time) in minutes:

> 120

With long-term contact:

Protective gloves in butyl rubber (EN 374).

Minimum layer thickness in mm:

> 0,7

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:



Page 5 of 10  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.03.2019 / 0011  
 Replacing version dated / version: 30.08.2018 / 0010  
 Valid from: 11.03.2019  
 PDF print date: 11.03.2019  
 Epoxy-Kleber 25 mL  
 Art.: 6183 (B)

Normally not necessary.  
 If fumes build up, use suitable breathing mask.  
 Filter A2 P2 (EN 14387), code colour brown, white  
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Viscous
Colour:	Light yellow
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	n.a.
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1,0-1,2 g/ml
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	>150 °C
Viscosity:	8000-16000 mPas (25°C, RV Spindel 6 (50 rpm) )
Explosive properties:	Not determined
Oxidising properties:	No

### 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 11.03.2019 / 0011

Replacing version dated / version: 30.08.2018 / 0010

Valid from: 11.03.2019

PDF print date: 11.03.2019

Epoxy-Kleber 25 mL

Art.: 6183 (B)

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

Strong heat

### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

#### Epoxy-Kleber 25 mL

Art.: 6183 (B)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

#### 3-trimethoxysilylpropane-1-thiol

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1940	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	6000	mg/kg	Rabbit		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Sensitising (skin contact)
Germ cell mutagenicity:						Negative
Symptoms:						mucous membrane irritation

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

#### Epoxy-Kleber 25 mL

Art.: 6183 (B)

Page 7 of 10  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.03.2019 / 0011  
 Replacing version dated / version: 30.08.2018 / 0010  
 Valid from: 11.03.2019  
 PDF print date: 11.03.2019  
 Epoxy-Kleber 25 mL  
 Art.: 6183 (B)

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

3-trimethoxysilylpropane-1-thiol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	439	mg/l	Brachydanio rerio		
12.1. Toxicity to daphnia:	EC50	48h	6,7	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	267	mg/l	Scenedesmus subspicatus		
12.2. Persistence and degradability:			51	%			Not readily biodegradable
Toxicity to bacteria:	EC10	3h	440	mg/l	activated sludge		

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

15 01 02 plastic packaging

15 01 04 metallic packaging

## SECTION 14: Transport information

### General statements

14.1. UN number: n.a.

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

n.a.

14.4. Packing group:

n.a.

Classification code:

n.a.

LQ:

n.a.

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

### Transport by sea (IMDG-code)

GB

Page 8 of 10  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.03.2019 / 0011  
 Replacing version dated / version: 30.08.2018 / 0010  
 Valid from: 11.03.2019  
 PDF print date: 11.03.2019  
 Epoxy-Kleber 25 mL  
 Art.: 6183 (B)

14.2. UN proper shipping name:  
 14.3. Transport hazard class(es): n.a.  
 14.4. Packing group: n.a.  
 Marine Pollutant: n.a.  
 14.5. Environmental hazards: Not applicable

**Transport by air (IATA)**

14.2. UN proper shipping name:  
 14.3. Transport hazard class(es): n.a.  
 14.4. Packing group: n.a.  
 14.5. Environmental hazards: Not applicable

**14.6. Special precautions for user**

Unless specified otherwise, general measures for safe transport must be followed.

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

Non-dangerous material according to Transport Regulations.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Observe restrictions:  
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!  
 Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): n.a.

**15.2 Chemical safety assessment**

A chemical safety assessment is not provided for mixtures.

**SECTION 16: Other information**

Revised sections: 2, 15  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

**Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):**

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Sens. 1, H317	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

- H302 Harmful if swallowed.
- H317 May cause an allergic skin reaction.
- H411 Toxic to aquatic life with long lasting effects.

- Skin Sens. — Skin sensitization
- Acute Tox. — Acute toxicity - oral
- Aquatic Chronic — Hazardous to the aquatic environment - chronic

**Any abbreviations and acronyms used in this document:**

- AC Article Categories
- acc., acc. to according, according to
- ACGIH American Conference of Governmental Industrial Hygienists

Page 9 of 10  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 11.03.2019 / 0011  
 Replacing version dated / version: 30.08.2018 / 0010  
 Valid from: 11.03.2019  
 PDF print date: 11.03.2019  
 Epoxy-Kleber 25 mL  
 Art.: 6183 (B)

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOEL Acceptable Operator Exposure Level  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)  
 BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)  
 BMGV Biological monitoring guidance value (EH40, UK)  
 BOD Biochemical oxygen demand  
 BSEF Bromine Science and Environmental Forum  
 bw body weight  
 CAS Chemical Abstracts Service  
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids  
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques  
 CIPAC Collaborative International Pesticides Analytical Council  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 COD Chemical oxygen demand  
 CTFA Cosmetic, Toiletry, and Fragrance Association  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 DOC Dissolved organic carbon  
 DT50 Dwell Time - 50% reduction of start concentration  
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EC European Community  
 ECHA European Chemicals Agency  
 EEA European Economic Area  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ERC Environmental Release Categories  
 ES Exposure scenario  
 etc. et cetera  
 EU European Union  
 EWC European Waste Catalogue  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane  
 HGWP Halocarbon Global Warming Potential  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC Intermediate Bulk Container  
 IBC (Code) International Bulk Chemical (Code)  
 IC Inhibitory concentration  
 IMDG-code International Maritime Code for Dangerous Goods  
 incl. including, inclusive  
 IUCLID International Uniform Chemical Information Database  
 LC lethal concentration  
 LC50 lethal concentration 50 percent kill  
 LCLo lowest published lethal concentration  
 LD Lethal Dose of a chemical

Page 10 of 10  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 11.03.2019 / 0011  
Replacing version dated / version: 30.08.2018 / 0010  
Valid from: 11.03.2019  
PDF print date: 11.03.2019  
Epoxy-Kleber 25 mL  
Art.: 6183 (B)

LD50 Lethal Dose, 50% kill  
LDLo Lethal Dose Low  
LOAEL Lowest Observed Adverse Effect Level  
LOEC Lowest Observed Effect Concentration  
LOEL Lowest Observed Effect Level  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
NIOSH National Institute of Occupational Safety and Health (United States of America)  
NOAEC No Observed Adverse Effective Concentration  
NOAEL No Observed Adverse Effect Level  
NOEC No Observed Effect Concentration  
NOEL No Observed Effect Level  
ODP Ozone Depletion Potential  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PAH polycyclic aromatic hydrocarbon  
PBT persistent, bioaccumulative and toxic  
PC Chemical product category  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
POCP Photochemical ozone creation potential  
ppm parts per million  
PROC Process category  
PTFE Polytetrafluorethylene  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SADT Self-Accelerating Decomposition Temperature  
SAR Structure Activity Relationship  
SU Sector of use  
SVHC Substances of Very High Concern  
Tel. Telephone  
ThOD Theoretical oxygen demand  
TOC Total organic carbon  
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).  
WHO World Health Organization  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.