


Girella con dado in ottone e guarnizione piatta in EPDM

Adaptor with union nut in brass and EPDM flat seal

Anschlussverschraubung mit EPDM-Flachdichtung und Messingmutter

Code	d - G (ISO 228)	L	Z	g	MOQ
S60QCVI-LBP	15-G $\frac{3}{4}$	42	14	82	50
S60QDVI-LBP	18-G $\frac{3}{4}$	42	14	83	50
S60REVI-LBP	22-G1	45	13	118	50
S60SFVI-LBP	28-G1 $\frac{1}{4}$	50	16	195	50
S60TGV I-LBP	35-G1 $\frac{1}{2}$	52	14	290	20
S60UHV I-LBP	42-G1 $\frac{3}{4}$	63	19	359	20
S60WJVI-LBP	54-G2 $\frac{3}{8}$	70	19	553	20




Girella con dado in ottone, raccordo femmina e guarnizione piatta in EPDM

Adaptor union with female thread, brass nut and EPDM flat seal

Übergangverschraubung I.G. mit EPDM-Flachdichtung und Messingmutter

Code	d - Rp	L	Z	g	MOQ
S62PCVI-LBP	15-Rp $\frac{1}{2}$	65	33	148	15
S62QCVI-LBP	15-Rp $\frac{3}{4}$	68	35	205	15
S62PDVI-LBP	18-Rp $\frac{1}{2}$	65	33	149	15
S62QDVI-LBP	18-Rp $\frac{3}{4}$	68	35	205	15
S62QEVI-LBP	22-Rp $\frac{3}{4}$	69	34	230	15
S62REVI-LBP	22-Rp1	73	36	279	15
S62RFVI-LBP	28-Rp1	77	39	432	15
S62SGVI-LBP	35-Rp1 $\frac{1}{4}$	81	37	529	15
S62THVI-LBP	42-Rp1 $\frac{1}{2}$	92	43	636	15
S62VJVI-LBP	54-Rp2	104	46	1.163	15



Girella con dado in ottone, raccordo maschio e guarnizione piatta in EPDM

Adaptor union with male thread, brass nut and EPDM flat seal

Übergangverschraubung A.G. mit EPDM-Flachdichtung und Messingmutter

Code	d - R	L	H	g	MOQ
S64PCVI-LBP	15-R $\frac{1}{2}$	69	48	150	15
S64QCVI-LBP	15-R $\frac{3}{4}$	72	51	177	15
S64PDVI-LBP	18-R $\frac{1}{2}$	69	48	150	15
S64QDVI-LBP	18-R $\frac{3}{4}$	72	51	178	15
S64PEVI-LBP	22-R $\frac{1}{2}$	73	50	252	15
S64QEVI-LBP	22-R $\frac{3}{4}$	75	52	228	15
S64REVI-LBP	22-R1	79	56	291	15
S64RFVI-LBP	28-R1	84	60	415	15
S64SGVI-LBP	35-R1 $\frac{1}{4}$	89	62	549	15
S64THVI-LBP	42-R1 $\frac{1}{2}$	100	68	679	15
S64VJVI-LBP	54-R2	113	76	1.141	15