

# Silicone Spray

## LOS 170

Silicone Spray is a fat-free lubricant, protective and parting agent as well as conditioner for plastics, wood, rubber and metals. Clean lubricating film that is not hardening. High resistance to temperatures. Protects from oxidation and corrosion and is water-repellent. Silicone Spray has a wide range of applications owing to its properties.

### Silicone Spray

- prevents the accumulation of adhesive residues on presses and guides
- prevents goods from adhering to conveyor belts, grooves, guideways and slides
- keeps rubber parts in good condition, they do not freeze, embrittle or adhere to other objects
- plastic parts appear in fresh gleam and do not embrittle
- makes sunroof and seat rails slide more easily
- excellent parting agent in moulding and injection moulding
- protects electric contacts from moisture
- makes jammed and squeaking parts run well again
- suitable as an assembly aid with tube connections

### Use:

Shake the aerosol vigorously before use. Clean and degrease the surface to be treated, then spray it from a distance of approx. 20-30cm and rub the substance in with a soft cloth.

### Technical Data:

Form:	Aerosol
Colour:	Colourless
Odour:	like solvent
Density (20°C):	0.62 g/ml
Ignition temperature:	>240°C
Temperature resistance:	max. 250°C
Solubility:	not water-soluble

**Content of aerosol can: 400 ml**

Suggestions, processing and use of our products correspond to the best knowledge at printing of this leaflet and are always given without obligation. You only can serve as a clue in consideration of the changing conditions; from this no liabilities, liability and guarantee claims can be derived. Own tests must be carried out before application. Every manufacturer of our products is liable for the retention everything legal to regulations.