

Page 1 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.05.2020 / 0003 Replacing version dated / version: 06.05.2019 / 0002 Valid from: 26.05.2020 PDF print date: 27.05.2020 Motorbike 4T 20W-50 Street 1 L Art.: 1500

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

# Motorbike 4T 20W-50 Street 1 L Art.: 1500

# **1.2** Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Motor oil

അ

Sector of use [SU]: SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites SU21 - Consumer uses: Private households (=general public = consumers) SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Chemical product category [PC]: PC17 - Hydraulic fluids PC24 - Lubricants, greases, release products Process category [PROC]: PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing) PROC20 - Use of functional fluids in small devices Article Categories [AC]: AC99 - Not required. Environmental Release Category [ERC]: ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC 7 - Use of functional fluid at industrial site ERC 9a - Widespread use of functional fluid (indoor) ERC 9b - Widespread use of functional fluid (outdoor) Uses advised against: No information available at present. 1.3 Details of the supplier of the safety data sheet LIQUI MOLY GmbH

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

## 1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)



Page 2 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.05.2020 / 0003 Replacing version dated / version: 06.05.2019 / 0002 Valid from: 26.05.2020 PDF print date: 27.05.2020 Motorbike 4T 20W-50 Street 1 L Art.: 1500

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

#### 2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %). The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC)

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

#### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substance

#### n.a. 3.2 Mixture

Distillates (petroleum), hydrotreated light paraffinic	
Registration number (REACH)	01-2119487077-29-XXXX
Index	649-468-00-3
EINECS, ELINCS, NLP	265-158-7
CAS	64742-55-8
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
Bis(nonylphenyl)amine	
Registration number (REACH)	01-2119488911-28-XXXX
Index	
EINECS, ELINCS, NLP	253-249-4
CAS	36878-20-3
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Chronic 4, H413
Baseoil - unspecified *	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Impurities, test data and additional information may have been taken into account in classifying and labelling the product. For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

\* The contained mineral oil can be described by one or more of the following numbers:

EINECS, ELINCS, NLP	Registration number (REACH)	Chemical name
265-157-1	01-2119484627-25-XXXX	Distillates (petroleum), hydrotreated heavy paraffinic
265-158-7	01-2119487077-29-XXXX	Distillates (petroleum), hydrotreated light paraffinic
265-169-7	01-2119471299-27-XXXX	Distillates (petroleum), solvent-dewaxed heavy paraffinic
265-159-2	01-2119480132-48-XXXX	Distillates (petroleum), solvent-dewaxed light paraffinic



Page 3 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.05.2020 / 0003 Replacing version dated / version: 06.05.2019 / 0002 Valid from: 26.05.2020 PDF print date: 27.05.2020 Motorbike 4T 20W-50 Street 1 L Art.: 1500

The substances named in this section are given with their actual, appropriate classification! For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

ആ

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. with long-term contact:

Drying of the skin.

Dermatitis (skin inflammation)

#### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

**SECTION 5: Firefighting measures** 

#### 5.1 Extinguishing media

#### Suitable extinguishing media

CO2

#### Dry extinguisher Foam

#### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Toxic gases

Flammable vapour/air mixtures

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

**SECTION 6: Accidental release measures** 

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air. Avoid contact with eyes or skin.



Page 4 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.05.2020 / 0003 Replacing version dated / version: 06.05.2019 / 0002 Valid from: 26.05.2020 PDF print date: 27.05.2020 Motorbike 4T 20W-50 Street 1 L Art.: 1500

#### If applicable, caution - risk of slipping. 6.2 Environmental precautions

If leakage occurs, dam up.

ആ

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Fill the absorbed material into lockable containers.

Do not wash away with water or watery cleaning agents.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation. Avoid formation of oil mist. Avoid contact with eyes. Avoid long lasting or intensive contact with skin. Do not carry cleaning cloths soaked in product in trouser pockets. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells. Store product closed and only in original packing. Protect from direct sunlight and warming. Store in a well ventilated place. Store in a dry place.

#### 7.3 Specific end use(s)

No information available at present.

**SECTION 8: Exposure controls/personal protection** 

#### 8.1 Control parameters

Chemical Name	Oil mist, mineral				Content %:
WEL-TWA: 5 mg/m3 (Mineral oil,	excluding metal	WEL-STEL:			
working fluids, ACGIH)					
Monitoring procedures:	-	Draeger - Oil Mist 1/a (67 33 031)			
BMGV:			Other information:	-	

Distillates (petroleum), hydro	otreated light paraffinic					
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - oral (animal		PNEC	9,33	mg/kg feed	
	feed)					
Consumer	Human - inhalation	Long term, local effects	DNEL	1,19	mg/m3	



Page 5 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.05.2020 / 0003 Replacing version dated / version: 06.05.2019 / 0002 Valid from: 26.05.2020 PDF print date: 27.05.2020 Motorbike 4T 20W-50 Street 1 L Art.: 1500

ആ

Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,97	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,7	mg/m3	

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	0,1	mg/l	
	Environment - marine		PNEC	0,01	mg/l	
	Environment - water,		PNEC	1	mg/l	
	sporadic (intermittent)				-	
	release					
	Environment - sewage		PNEC	1	mg/l	
	treatment plant					
	Environment - sediment,		PNEC	132000	mg/kg dw	
	freshwater					
	Environment - sediment,		PNEC	13200	mg/kg dw	
	marine					
	Environment - soil		DNEL	263000	mg/kg dw	
	Environment - periodic		PNEC	1	mg/kg	
	release					
Consumer	Human - oral	Long term, systemic	DNEL	0,31	mg/kg	
		effects			bw/day	
Consumer	Human - inhalation	Long term, systemic	DNEL	1,09	mg/m3	
		effects				
Consumer	Human - dermal	Long term, systemic	DNEL	0,31	mg/kg	
		effects			bw/day	
Workers / employees	Human - dermal	Long term, systemic	DNEL	0,62	mg/kg	
		effects			bw/day	
Workers / employees	Human - inhalation	Long term, systemic	DNEL	4,37	mg/m3	
		effects				

Distillates (petroleum), hydro	otreated heavy paraffinic					
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental		-			
	compartment					
	Environment - oral (animal		PNEC	9,33	mg/kg	
	feed)					

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).
(11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit

value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

#### 8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.



Page 6 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.05.2020 / 0003 Replacing version dated / version: 06.05.2019 / 0002 Valid from: 26.05.2020 PDF print date: 27.05.2020 Motorbike 4T 20W-50 Street 1 L Art.: 1500

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

ആ

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection: Chemical resistant protective gloves (EN 374). If applicable Protective nitrile gloves (EN 374). Minimum layer thickness in mm: 0,5

Permeation time (penetration time) in minutes: 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Filter A P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

## 8.2.3 Environmental exposure controls

No information available at present.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state: Colour: Odour: Odour threshold: pH-value: Melting point/freezing point: Initial boiling point and boiling range: roperties Liquid Brown Characteristic Not determined Not determined Not determined Not determined



Page 7 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.05.2020 / 0003 Replacing version dated / version: 06.05.2019 / 0002 Valid from: 26.05.2020

ആ

PDF print date: 27.05.2020 Motorbike 4T 20W-50 Street 1 L Art.: 1500

Flash point: Evaporation rate: Flammability (solid, gas): Lower explosive limit: Upper explosive limit: Vapour pressure: Vapour density (air = 1): . Density: Bulk density: Solubility(ies): Water solubility: Partition coefficient (n-octanol/water): Auto-ignition temperature: Decomposition temperature: Viscosity: Viscosity: Explosive properties: Oxidising properties:

## 9.2 Other information

Miscibility: Fat solubility / solvent: Conductivity: Surface tension: Solvents content:

250 °C Not determined n.a. Not determined Not determined Not determined Not determined 0,87 g/ml n.a. Not determined Insoluble Not determined Not determined Not determined 166,6 mm2/s (40°C) 19,76 mm2/s (100°C) Product is not explosive. No

Not determined Not determined Not determined Not determined

#### **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** Open flame, ignition sources **10.5 Incompatible materials** Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products** 

No decomposition when used as directed.

**SECTION 11: Toxicological information** 

#### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification). Motorbike 4T 20W-50 Street 1 L

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						



Page 8 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.05.2020 / 0003 Replacing version dated / version: 06.05.2019 / 0002 Valid from: 26.05.2020 PDF print date: 27.05.2020 Motorbike 4T 20W-50 Street 1 L Art.: 1500

œ

Serious eye damage/irritation:

Specific target organ toxicity -			n.d.a.
repeated exposure (STOT-RE):			
Aspiration hazard:			n.d.a.
Symptoms:			n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
reate toxicity, by ordiroute.	2000	20000	lg/ikg		Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	501101031011
i cato toxicity, by domina routo.	2200	20000			Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute	Aerosol,
	2000	- 0,00		- Tur	Inhalation Toxicity)	Analogous
					initial and in toxicity)	conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant.
				Rabbit	Dermal	Analogous
					Irritation/Corrosion)	conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant,
conoue eye damago, matem				Rabbit	Irritation/Corrosion)	Analogous
						conclusion
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact),
						Analogous
						conclusion
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
com con matagomony.				typhimurium	Reverse Mutation Test)	Analogous
						conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative,
com don matagomoty.					Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	56161600011
Carcinogenicity:				Mouse	OECD 451	Negative,
earoniogeniony.				Modoe	(Carcinogenicity Studies)	Analogous
					(Carolinogeriloity Ctaales)	conclusion
Reproductive toxicity:				Rat	OECD 421	Negative,
Repredative texterty.				- Tur	(Reproduction/Developm	Analogous
					ental Toxicity Screening	conclusion
					Test)	conclusion
Reproductive toxicity				Rat	OECD 414 (Prenatal	Negative,
(Developmental toxicity):				- Tur	Developmental Toxicity	Analogous
(Developmental texterty).					Study)	conclusion
Aspiration hazard:						Yes
Specific target organ toxicity -	NOAEL	125	mg/kg	Rat	OECD 408 (Repeated	Analogous
repeated exposure (STOT-RE),			bw/d		Dose 90-Day Oral	conclusion
oral:			2		Toxicity Study in	201101001011
					Rodents)	
Specific target organ toxicity -	NOAEL	1000	mg/kg	Rabbit	OECD 410 (Repeated	Analogous
repeated exposure (STOT-RE),					Dose Dermal Toxicity -	conclusion
dermal:					90-Day)	2 3.10.00.011
	1	1	1	1		
Bis(nonylphenyl)amine						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
			33		Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	Analogous
					Dermal Toxicity)	conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Analogous
					Irritation/Corrosion)	conclusion
	1	1		Rabbit	OFCD 405 (Acute Eve	Not irritant

Irritation/Corrosion)

OECD 405 (Acute Eye

Not irritant, Analogous conclusion

Rabbit



Page 9 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.05.2020 / 0003 Replacing version dated / version: 06.05.2019 / 0002 Valid from: 26.05.2020 PDF print date: 27.05.2020 Motorbike 4T 20W-50 Street 1 L Art.: 1500

œ

Despiratory or alvia				Cuines nim		No. (olivo
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact),
						Analogous
						conclusion
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
				typhimurium	Reverse Mutation Test)	Analogous
						conclusion
Germ cell mutagenicity:				Mouse	OECD 478 (Genetic	Negative,
					Toxicology - Rodent	Analogous
					dominant Lethal Test)	conclusion
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative,
					Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	
Reproductive toxicity	NOAEL	150	mg/kg	Rat	OECD 414 (Prenatal	Negative
(Developmental toxicity):			bw/d		Developmental Toxicity	
					Study)	
Specific target organ toxicity -	NOAEL	<100	mg/kg	Rat	OECD 408 (Repeated	
repeated exposure (STOT-RE),			bw/d		Dose 90-Day Oral	
oral:					Toxicity Study in	
					Rodents)	

## **SECTION 12: Ecological information**

/lotorbike 4T 20W-50 Str	eet 1 L						
Art.: 1500							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Other adverse							n.d.a.
effects:							

oxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	28d	>1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	14d	1000	mg/l	Oncorhynchus mykiss	QSÁR	
12.3. Bioaccumulative potential:							Not to be expected
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion



Page 10 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.05.2020 / 0003 Replacing version dated / version: 06.05.2019 / 0002 Valid from: 26.05.2020 PDF print date: 27.05.2020 Motorbike 4T 20W-50 Street 1 L Art.: 1500

œ

12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	31	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable, Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		>6				@20°C
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to algae:	NOEC/NOEL	72h	>10	mg/l	Desmodesmus subspicatus		Analogous conclusion
12.2. Persistence and degradability:		28d	24	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Not readily biodegradable
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	600	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	1	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable, Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		>7,6				Concentration ir organisms possible.
12.3. Bioaccumulative potential:	BCF		1730				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion

# **SECTION 13: Disposal considerations**

13.1 Waste treatment methods



Page 11 of 13

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.05.2020 / 0003 Replacing version dated / version: 06.05.2019 / 0002 Valid from: 26.05.2020 PDF print date: 27.05.2020 Motorbike 4T 20W-50 Street 1 L Art.: 1500

#### For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no .: The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU) 13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations. E.g. dispose at suitable refuse site. E.g. suitable incineration plant. For contaminated packing material Pay attention to local and national official regulations. 15 01 01 paper and cardboard packaging 15 01 02 plastic packaging 15 01 04 metallic packaging Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance. **SECTION 14: Transport information** 

4.1. UN number:	n.a.
ransport by road/by rail (ADR/RID)	
4.2. UN proper shipping name:	
4.3. Transport hazard class(es):	n.a.
4.4. Packing group:	n.a.
Classification code:	n.a.
Q:	n.a.
4.5. Environmental hazards:	Not applicable
unnel restriction code:	
ransport by sea (IMDG-code)	
4.2. UN proper shipping name:	
4.3. Transport hazard class(es):	n.a.
4.4. Packing group:	n.a.
farine Pollutant:	n.a
4.5. Environmental hazards:	Not applicable
ransport by air (IATA)	
4.2. UN proper shipping name:	
4.3. Transport hazard class(es):	n.a.
4.4. Packing group:	n.a.
4.5. Environmental hazards:	Not applicable

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions: General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):



Page 12 of 13

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.05.2020 / 0003 Replacing version dated / version: 06.05.2019 / 0002 Valid from: 26.05.2020 PDF print date: 27.05.2020 Motorbike 4T 20W-50 Street 1 L Art.: 1500

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

**Revised sections:** 

3, 11, 12, 15

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP): Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways. H413 May cause long lasting harmful effects to aquatic life.

Asp. Tox. — Aspiration hazard Aquatic Chronic — Hazardous to the aquatic environment - chronic

#### Any abbreviations and acronyms used in this document:

according, according to acc., acc. to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Article number Art., Art. no. ASTM ASTM International (American Society for Testing and Materials) Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) The International Bromine Council BSEF body weight hw CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. ЕČ European Community ECHA European Chemicals Agency European Economic Community EEC EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances ΕN **European Norms** EPA United States Environmental Protection Agency (United States of America) etc. et cetera FU European Union EVAL Ethylene-vinyl alcohol copolymer Fax number Fax. gen. general Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential IARC International Agency for Research on Cancer IATA International Air Transport Association International Bulk Chemical (Code) IBC (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl.



ആ Page 13 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.05.2020 / 0003 Replacing version dated / version: 06.05.2019 / 0002 Valid from: 26.05.2020 PDF print date: 27.05.2020 Motorbike 4T 20W-50 Street 1 L Art.: 1500 IUCLID International Uniform Chemical Information Database LQ Limited Quantities International Convention for the Prevention of Marine Pollution from Ships MARPOL not applicable n.a. not available n.av. n.c. not checked n.d.a. no data available OECD Organisation for Economic Co-operation and Development org. organic PBT persistent, bioaccumulative and toxic PF Polyethylene PNEC Predicted No Effect Concentration parts per million ppm PVC Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Telephone Tel. United Nations Recommendations on the Transport of Dangerous Goods UN RTDG VOC Volatile organic compounds very persistent and very bioaccumulative vPvB wet weight wwt The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.