

(B)

Page 1 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.07.2020 / 0016

Replacing version dated / version: 12.02.2018 / 0015

Valid from: 07.07.2020 PDF print date: 10.07.2020 HYPOID GETR.GL5 80W 500 mL

Art.: 1402

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

HYPOID GETR.GL5 80W 500 mL

Art.: 1402

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC17 - Hydraulic fluids

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC20 - Use of functional fluids in small devices

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 9a - Widespread use of functional fluid (indoor)

ERC 9b - Widespread use of functional fluid (outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0

Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification



Page 2 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.07.2020 / 0016

Replacing version dated / version: 12.02.2018 / 0015

Valid from: 07.07.2020 PDF print date: 10.07.2020 HYPOID GETR.GL5 80W 500 mL

Art.: 1402

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivatives. May produce an allergic reaction.

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. **3.2 Mixture**

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid	Substance with specific conc. limit(s) acc. to REACh-
with phosphorus oxide, propylene oxide and amines, C12-14-alkyl	registration
(branched)	
Registration number (REACH)	01-2119493620-38-XXXX
Index	
EINECS, ELINCS, NLP	931-384-6 (REACH-IT List-No.)
CAS	
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302
	Skin Sens. 1, H317
	Eye Dam. 1, H318
	Aquatic Chronic 2, H411

Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde	SVHC-substance
and phenol, heptyl derivatives	
Registration number (REACH)	01-2119971727-23-XXXX
Index	
EINECS, ELINCS, NLP	939-460-0 (REACH-IT List-No.)
CAS	
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226
	Skin Irrit. 2, H315
	Eye Dam. 1, H318
	Skin Sens. 1B, H317
	Aquatic Chronic 3, H412

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.



(B)

Page 3 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.07.2020 / 0016

Replacing version dated / version: 12.02.2018 / 0015

Valid from: 07.07.2020 PDF print date: 10.07.2020 HYPOID GETR.GL5 80W 500 mL

Art.: 1402

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Drying of the skin.

Irritation of the skin.

Allergic reaction

4.3 Indication of any immediate medical attention and special treatment needed

n.c

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO2

Foam

Dry extinguisher

Unsuitable extinguishing media

High volume water jet

Water jet spray

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Oxides of sulphur

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of oil mist.

Remove possible causes of ignition - do not smoke.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.



(B)

Page 4 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.07.2020 / 0016 Replacing version dated / version: 12.02.2018 / 0015

Valid from: 07.07.2020 PDF print date: 10.07.2020 HYPOID GETR.GL5 80W 500 mL

Art.: 1402

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Do not heat to temperatures close to flash point.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with flammable or self-igniting materials.

Protect against moisture and store closed.

Under all circumstances prevent penetration into the soil.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Oil mist, mineral			Content %:
WEL-TWA: 5 mg/m3 (Mineral o	il, excluding metal	WEL-STEL:		
working fluids, ACGIH)				
Monitoring procedures:	-	Draeger - Oil Mist 1/a (67 33 031)		
BMGV:			Other information:	

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.



Page 5 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.07.2020 / 0016

Replacing version dated / version: 12.02.2018 / 0015

Valid from: 07.07.2020 PDF print date: 10.07.2020 HYPOID GETR.GL5 80W 500 mL

Art.: 1402

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection:

Protective nitrile gloves (EN 374).

Permeation time (penetration time) in minutes:

480

Minimum layer thickness in mm:

0,4

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

With oil mist formation:

Filter A P3 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to

manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Liquid



Page 6 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.07.2020 / 0016

Replacing version dated / version: 12.02.2018 / 0015

Valid from: 07.07.2020 PDF print date: 10.07.2020 HYPOID GETR.GL5 80W 500 mL

Art.: 1402

Colour: Brown Odour: Characteristic Odour threshold: Not determined

pH-value:

Melting point/freezing point: Not determined Initial boiling point and boiling range: Not determined Flash point: 204-222 °C Evaporation rate: Not determined

Flammability (solid, gas): n.a.

Lower explosive limit: Not determined Upper explosive limit: Not determined Vapour pressure: Not determined Vapour density (air = 1): Not determined Density: 0,90-0,91 g/ml Bulk density: n.a. Solubility(ies): Not determined

Water solubility: Insoluble Partition coefficient (n-octanol/water): Not determined Auto-ignition temperature: Not determined Decomposition temperature: Not determined 98-400 mm2/s (40°C) Viscosity: Viscosity: 11,3-28 mm2/s (100°C)

Explosive properties: Product is not explosive. Oxidising properties:

9.2 Other information

Miscibility: Not determined Fat solubility / solvent: Not determined Conductivity: Not determined Surface tension: Not determined Solvents content: Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Protect from humidity.

Open flame, ignition sources

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

HYPOID GETR.GL5 80W 500 m Art.: 1402	L					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>5000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.



Page 7 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 07.07.2020 / 0016

Replacing version dated / version: 12.02.2018 / 0015

Valid from: 07.07.2020 PDF print date: 10.07.2020 HYPOID GETR.GL5 80W 500 mL Art.: 1402

Acute toxicity, by inhalation:	n.d.a.
Skin corrosion/irritation:	n.d.a.
Serious eye damage/irritation:	n.d.a.
Respiratory or skin	n.d.a.
sensitisation:	
Germ cell mutagenicity:	n.d.a.
Carcinogenicity:	n.d.a.
Reproductive toxicity:	n.d.a.
Specific target organ toxicity -	n.d.a.
single exposure (STOT-SE):	
Specific target organ toxicity -	n.d.a.
repeated exposure (STOT-RE):	
Aspiration hazard:	n.d.a.
Symptoms:	n.d.a.
Other information:	Classification
	according to
	calculation
	procedure.

Reaction products of bis(4-me	thylpentan-2-y	/l)dithiophosp	phoric acid with	n phosphorus ox	ide, propylene oxide and ar	nines, C12-14-
alkyl (branched)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	· ·	Corrosive
Respiratory or skin				Mouse	OECD 429 (Skin	Sensitising
sensitisation:					Sensitisation - Local	
					Lymph Node Assay)	

Reaction product of 1,3,4-thiad	iazolidine-2,5-	dithione, for	naldehyde and	phenol, heptyl c	lerivatives	
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	<5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit		Irritant
Serious eye damage/irritation:				Rabbit		Eye Dam. 1

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Other adverse							n.d.a.
effects:							



Page 8 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 07.07.2020 / 0016

Replacing version dated / version: 12.02.2018 / 0015

Valid from: 07.07.2020 PDF print date: 10.07.2020 HYPOID GETR.GL5 80W 500 mL Art.: 1402

Other information:			Environmental
			hazards: Not
			applicable No
			classification
			based on test
			data.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	96h	3,2	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	91,4	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	96h	6,4	mg/l	Selenastrum capricornutum	OEĆD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	96h	1,7	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	7,4	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
Toxicity to bacteria:	EC50	3h	~2433	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	26	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	75	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	25	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:	DOC	28d	17,4	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
12.3. Bioaccumulative potential:	Log Kow		>9,4			,	

SECTION 13: Disposal considerations

13.1 Waste treatment methods



Page 9 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.07.2020 / 0016
Replacing version dated / version: 12.02.2018 /

Replacing version dated / version: 12.02.2018 / 0015

Valid from: 07.07.2020 PDF print date: 10.07.2020 HYPOID GETR.GL5 80W 500 mL

Art.: 1402

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

15 01 04 metallic packaging

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LQ:n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):
14.4. Packing group:
n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Yes

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 4,42 %



®

Page 10 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.07.2020 / 0016

Replacing version dated / version: 12.02.2018 / 0015

Valid from: 07.07.2020 PDF print date: 10.07.2020 HYPOID GETR.GL5 80W 500 mL

Art.: 1402

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

15

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Acute Tox. — Acute toxicity - oral

Skin Sens. — Skin sensitization

Eye Dam. — Serious eye damage

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Flam. Liq. — Flammable liquid

Skin Irrit. — Skin irritation

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency
EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera EU European Union

EVAL Ethylene-vinyl alcohol copolymer



Page 11 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.07.2020 / 0016

Replacing version dated / version: 12.02.2018 / 0015

Valid from: 07.07.2020 PDF print date: 10.07.2020 HYPOID GETR.GL5 80W 500 mL

Art.: 1402

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International

Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern

SVHC Substances of Very F

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.