

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**HYPOID GET.(GL5)85W90 205 L**  
**Art.: 2165**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Gear lubricant

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC17 - Hydraulic fluids

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC20 - Use of functional fluids in small devices

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 9a - Widespread use of functional fluid (indoor)

ERC 9b - Widespread use of functional fluid (outdoor)

#### **Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH

Jerg-Wieland-Str. 4

89081 Ulm-Lehr

Tel.: (+49) 0731-1420-0

Fax: (+49) 0731-1420-88

Qualified person's e-mail address: [info@chemical-check.de](mailto:info@chemical-check.de), [k.schnurbusch@chemical-check.de](mailto:k.schnurbusch@chemical-check.de) Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (LMR)

### SECTION 2: Hazards identification

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 06.07.2020 / 0018  
 Replacing version dated / version: 12.02.2018 / 0017  
 Valid from: 06.07.2020  
 PDF print date: 10.07.2020  
 HYPOID GET.(GL5)85W90 205 L  
 Art.: 2165

## 2.1 Classification of the substance or mixture

### Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

## 2.2 Label elements

### Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivatives. May produce an allergic reaction.

EUH210-Safety data sheet available on request.

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange.

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

| Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) | Substance with specific conc. limit(s) acc. to REACH-registration   |
|---|---|
| Registration number (REACH)   | 01-2119493620-38-XXXX   |
| Index   | ---   |
| EINECS, ELINCS, NLP   | 931-384-6 (REACH-IT List-No.)   |
| CAS   | ---   |
| content %   | 1-<2,5  |
| Classification according to Regulation (EC) 1272/2008 (CLP)   | Acute Tox. 4, H302<br>Skin Sens. 1, H317<br>Eye Dam. 1, H318<br>Aquatic Chronic 2, H411                         |
| Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivatives   | SVHC-substance  |
| Registration number (REACH)   | 01-2119971727-23-XXXX   |
| Index   | ---   |
| EINECS, ELINCS, NLP   | 939-460-0 (REACH-IT List-No.)   |
| CAS   | ---   |
| content %   | 0,1-<1  |
| Classification according to Regulation (EC) 1272/2008 (CLP)   | Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>Skin Sens. 1B, H317<br>Aquatic Chronic 3, H412 |

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.  
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.  
Do not induce vomiting. Consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.  
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Drying of the skin.

Irritation of the skin.

Allergic reaction possible.

### 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

CO<sub>2</sub>  
Foam  
Dry extinguisher  
Water jet spray

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon  
Oxides of nitrogen  
Oxides of sulphur

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary.  
Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of oil mist.  
Remove possible causes of ignition - do not smoke.  
Avoid inhalation, and contact with eyes or skin.  
If applicable, caution - risk of slipping.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 06.07.2020 / 0018  
 Replacing version dated / version: 12.02.2018 / 0017  
 Valid from: 06.07.2020  
 PDF print date: 10.07.2020  
 HYPOID GET.(GL5)85W90 205 L  
 Art.: 2165

## 6.2 Environmental precautions

If leakage occurs, dam up.  
 Resolve leaks if this possible without risk.  
 Prevent from entering drainage system.  
 Prevent surface and ground-water infiltration, as well as ground penetration.  
 If accidental entry into drainage system occurs, inform responsible authorities.

## 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

## 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

# SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

## 7.1 Precautions for safe handling

### 7.1.1 General recommendations

Ensure good ventilation.  
 Keep away from sources of ignition - Do not smoke.  
 Avoid contact with eyes or skin.  
 Do not carry cleaning cloths soaked in product in trouser pockets.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Do not heat to temperatures close to flash point.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

## 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.  
 Store product closed and only in original packing.  
 Do not store with flammable or self-igniting materials.  
 Protect against moisture and store closed.  
 Under all circumstances prevent penetration into the soil.

## 7.3 Specific end use(s)

No information available at present.

# SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

| Chemical Name   | Oil mist, mineral                    | Content %:             |
|---|--------------------------------------|------------------------|
| WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal working fluids, ACGIH) | WEL-STEL: ---                        | ---                    |
| Monitoring procedures:  | - Draeger - Oil Mist 1/a (67 33 031) |                        |
| BMGV: ---   |                                      | Other information: --- |

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

Page 5 of 11  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 06.07.2020 / 0018  
Replacing version dated / version: 12.02.2018 / 0017  
Valid from: 06.07.2020  
PDF print date: 10.07.2020  
HYPOID GET.(GL5)85W90 205 L  
Art.: 2165

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
Applies only if maximum permissible exposure values are listed here.  
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
These are specified by e.g. BS EN 14042.  
BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection:  
Protective nitrile gloves (EN 374).  
Minimum layer thickness in mm:  
0,35  
Permeation time (penetration time) in minutes:  
>= 480  
Protective hand cream recommended.  
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:  
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
Normally not necessary.  
With oil mist formation:  
Filter A P3 (EN 14387), code colour brown, white  
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
Not applicable

Additional information on hand protection - No tests have been performed.  
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
Selection of materials derived from glove manufacturer's indications.  
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Page 6 of 11  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 06.07.2020 / 0018  
 Replacing version dated / version: 12.02.2018 / 0017  
 Valid from: 06.07.2020  
 PDF print date: 10.07.2020  
 HYPOID GET.(GL5)85W90 205 L  
 Art.: 2165

|  |                                 |
|--|---------------------------------|
| Physical state:                          | Liquid                          |
| Colour:                                  | Brown                           |
| Odour:                                   | Characteristic                  |
| Odour threshold:                         | Not determined                  |
| pH-value:                                | n.a.                            |
| Melting point/freezing point:            | Not determined                  |
| Initial boiling point and boiling range: | Not determined                  |
| Flash point:                             | 206 °C                          |
| Evaporation rate:                        | Not determined                  |
| Flammability (solid, gas):               | n.a.                            |
| Lower explosive limit:                   | Not determined                  |
| Upper explosive limit:                   | Not determined                  |
| Vapour pressure:                         | Not determined                  |
| Vapour density (air = 1):                | Not determined                  |
| Density:                                 | 0,9 g/ml                        |
| Bulk density:                            | n.a.                            |
| Solubility(ies):                         | Not determined                  |
| Water solubility:                        | Insoluble                       |
| Partition coefficient (n-octanol/water): | Not determined                  |
| Auto-ignition temperature:               | Not determined                  |
| Decomposition temperature:               | Not determined                  |
| Viscosity:                               | 201 mm <sup>2</sup> /s (40°C)   |
| Viscosity:                               | 17,5 mm <sup>2</sup> /s (100°C) |
| Explosive properties:                    | Product is not explosive.       |
| Oxidising properties:                    | No                              |
| <b>9.2 Other information</b>             |                                 |
| Miscibility:                             | Not determined                  |
| Fat solubility / solvent:                | Not determined                  |
| Conductivity:                            | Not determined                  |
| Surface tension:                         | Not determined                  |
| Solvents content:                        | Not determined                  |

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

Protect from humidity.

Open flame, ignition sources

### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

HYPOID GET.(GL5)85W90 205 L

Art.: 2165

| Toxicity / effect              | Endpoint | Value | Unit  | Organism | Test method | Notes            |
|--------------------------------|----------|-------|-------|----------|-------------|------------------|
| Acute toxicity, by oral route: | ATE      | >5000 | mg/kg |          |             | calculated value |

Page 7 of 11  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 06.07.2020 / 0018  
 Replacing version dated / version: 12.02.2018 / 0017  
 Valid from: 06.07.2020  
 PDF print date: 10.07.2020  
 HYPOID GET.(GL5)85W90 205 L  
 Art.: 2165

|   |  |  |  |  |  |  |
|---|--|--|--|--|--|--|
| Acute toxicity, by dermal route:                              |  |  |  |  |  | n.d.a.   |
| Acute toxicity, by inhalation:                                |  |  |  |  |  | n.d.a.   |
| Skin corrosion/irritation:                                    |  |  |  |  |  | n.d.a.   |
| Serious eye damage/irritation:                                |  |  |  |  |  | n.d.a.   |
| Respiratory or skin sensitisation:                            |  |  |  |  |  | n.d.a.   |
| Germ cell mutagenicity:                                       |  |  |  |  |  | n.d.a.   |
| Carcinogenicity:  |  |  |  |  |  | n.d.a.   |
| Reproductive toxicity:  |  |  |  |  |  | n.d.a.   |
| Specific target organ toxicity - single exposure (STOT-SE):   |  |  |  |  |  | n.d.a.   |
| Specific target organ toxicity - repeated exposure (STOT-RE): |  |  |  |  |  | n.d.a.   |
| Aspiration hazard:  |  |  |  |  |  | n.d.a.   |
| Symptoms:   |  |  |  |  |  | n.d.a.   |
| Other information:  |  |  |  |  |  | Classification according to calculation procedure. |

#### Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

| Toxicity / effect                  | Endpoint | Value | Unit  | Organism | Test method  | Notes        |
|------------------------------------|----------|-------|-------|----------|--|--------------|
| Acute toxicity, by oral route:     | LD50     | >2000 | mg/kg | Rat      | OECD 401 (Acute Oral Toxicity)                         |              |
| Skin corrosion/irritation:         |          |       |       | Rabbit   | OECD 404 (Acute Dermal Irritation/Corrosion)           | Not irritant |
| Serious eye damage/irritation:     |          |       |       | Rabbit   |  | Corrosive    |
| Respiratory or skin sensitisation: |          |       |       | Mouse    | OECD 429 (Skin Sensitisation - Local Lymph Node Assay) | Sensitising  |

#### Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivatives

| Toxicity / effect                | Endpoint | Value | Unit  | Organism | Test method                      | Notes      |
|----------------------------------|----------|-------|-------|----------|----------------------------------|------------|
| Acute toxicity, by oral route:   | LD50     | <5000 | mg/kg | Rat      |                                  |            |
| Acute toxicity, by dermal route: | LD50     | >2000 | mg/kg | Rat      | OECD 402 (Acute Dermal Toxicity) |            |
| Skin corrosion/irritation:       |          |       |       | Rabbit   |                                  | Irritant   |
| Serious eye damage/irritation:   |          |       |       | Rabbit   |                                  | Eye Dam. 1 |

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

#### HYPOID GET.(GL5)85W90 205 L

Art.: 2165

| Toxicity / effect                        | Endpoint | Time | Value | Unit | Organism | Test method | Notes                                     |
|--|----------|------|-------|------|----------|-------------|---|
| 12.1. Toxicity to fish:                  |          |      |       |      |          |             | n.d.a.                                    |
| 12.1. Toxicity to daphnia:               |          |      |       |      |          |             | n.d.a.                                    |
| 12.1. Toxicity to algae:                 |          |      |       |      |          |             | n.d.a.                                    |
| 12.2. Persistence and degradability:     |          |      |       |      |          |             | n.d.a.                                    |
| 12.3. Bioaccumulative potential:         |          |      |       |      |          |             | n.d.a.                                    |
| 12.4. Mobility in soil:                  |          |      |       |      |          |             | n.d.a.                                    |
| 12.5. Results of PBT and vPvB assessment |          |      |       |      |          |             | n.d.a.                                    |
| 12.6. Other adverse effects:             |          |      |       |      |          |             | n.d.a.                                    |
| Other information:                       |          |      |       |      |          |             | According to the recipe, contains no AOX. |

Page 8 of 11  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 06.07.2020 / 0018  
 Replacing version dated / version: 12.02.2018 / 0017  
 Valid from: 06.07.2020  
 PDF print date: 10.07.2020  
 HYPOID GET.(GL5)85W90 205 L  
 Art.: 2165

**Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)**

| Toxicity / effect                    | Endpoint  | Time | Value | Unit | Organism                  | Test method  | Notes |
|--------------------------------------|-----------|------|-------|------|---------------------------|--|-------|
| 12.1. Toxicity to fish:              | NOEC/NOEL | 96h  | 3,2   | mg/l | Oncorhynchus mykiss       | OECD 203 (Fish, Acute Toxicity Test)   |       |
| 12.1. Toxicity to daphnia:           | EC50      | 48h  | 91,4  | mg/l | Daphnia magna             | OECD 202 (Daphnia sp. Acute Immobilisation Test)   |       |
| 12.1. Toxicity to algae:             | EC50      | 96h  | 6,4   | mg/l | Selenastrum capricornutum | OECD 201 (Alga, Growth Inhibition Test)  |       |
| 12.1. Toxicity to algae:             | NOEC/NOEL | 96h  | 1,7   | mg/l | Selenastrum capricornutum | OECD 201 (Alga, Growth Inhibition Test)  |       |
| 12.2. Persistence and degradability: |           | 28d  | 7,4   | %    | activated sludge          | OECD 301 B (Ready Biodegradability - Co2 Evolution Test)                                 |       |
| Toxicity to bacteria:                | EC50      | 3h   | ~2433 | mg/l | activated sludge          | OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation)) |       |

**Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivatives**

| Toxicity / effect                    | Endpoint | Time | Value | Unit | Organism                        | Test method  | Notes |
|--------------------------------------|----------|------|-------|------|---------------------------------|--|-------|
| 12.1. Toxicity to fish:              | LL50     | 96h  | 26    | mg/l | Oncorhynchus mykiss             | OECD 203 (Fish, Acute Toxicity Test)                     |       |
| 12.1. Toxicity to daphnia:           | EL50     | 48h  | 75    | mg/l | Daphnia magna                   | OECD 202 (Daphnia sp. Acute Immobilisation Test)         |       |
| 12.1. Toxicity to algae:             | EC50     | 72h  | 25    | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test)                  |       |
| 12.2. Persistence and degradability: | DOC      | 28d  | 17,4  | %    |                                 | OECD 301 B (Ready Biodegradability - Co2 Evolution Test) |       |
| 12.3. Bioaccumulative potential:     | Log Kow  |      | >9,4  |      |                                 |  |       |

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)



Page 9 of 11  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 06.07.2020 / 0018  
 Replacing version dated / version: 12.02.2018 / 0017  
 Valid from: 06.07.2020  
 PDF print date: 10.07.2020  
 HYPOID GET.(GL5)85W90 205 L  
 Art.: 2165

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils  
 Recommendation:

Sewage disposal shall be discouraged.  
 Pay attention to local and national official regulations.  
 Implement substance recycling.  
 E.g. suitable incineration plant.

### For contaminated packing material

Pay attention to local and national official regulations.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

15 01 04 metallic packaging

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number: n.a.

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

### Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 4,42 %

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 06.07.2020 / 0018  
 Replacing version dated / version: 12.02.2018 / 0017  
 Valid from: 06.07.2020  
 PDF print date: 10.07.2020  
 HYPOID GET.(GL5)85W90 205 L  
 Art.: 2165

## Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.  
 H317 May cause an allergic skin reaction.  
 H302 Harmful if swallowed.  
 H315 Causes skin irritation.  
 H318 Causes serious eye damage.  
 H411 Toxic to aquatic life with long lasting effects.  
 H412 Harmful to aquatic life with long lasting effects.

Acute Tox. — Acute toxicity - oral  
 Skin Sens. — Skin sensitization  
 Eye Dam. — Serious eye damage  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic  
 Flam. Liq. — Flammable liquid  
 Skin Irrit. — Skin irritation

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ASTM ASTM International (American Society for Testing and Materials)  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BSEF The International Bromine Council  
 bw body weight  
 CAS Chemical Abstracts Service  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EC European Community  
 ECHA European Chemicals Agency  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 etc. et cetera  
 EU European Union  
 EVAL Ethylene-vinyl alcohol copolymer  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC (Code) International Bulk Chemical (Code)

Page 11 of 11  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 06.07.2020 / 0018  
Replacing version dated / version: 12.02.2018 / 0017  
Valid from: 06.07.2020  
PDF print date: 10.07.2020  
HYPOID GET.(GL5)85W90 205 L  
Art.: 2165

IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCID International Uniform Chemical Information Database  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PBT persistent, bioaccumulative and toxic  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
ppm parts per million  
PVC Polyvinylchloride  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC Substances of Very High Concern  
Tel. Telephone  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.