

# Technical Datasheet



Trade name : Stripper  
Reviewed: 27.02.2020  
Date of print : 27.02.2020

Page : 1 of 1

## Description

Stripper is a mild alkaline, aqueous cleaner to remove water-based paint and varnish, bitumen, impregnation compounds, coatings, sealings, synthetic residues and waxes.

## Chemical characterisation

Water-based light alkaline cleaning agent.

## Classification according to Regulation (EC) No.1272/2008 [CLP]

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2A ; Causes serious eye irritation.  
Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

## Transport information

ADR : -

## Water hazard class (Classification according to AwSV)

Water hazard class : 2 (significant hazardous to water)

## Labelling for contents according to regulation (EC) No. 648/2004

5 - 15 % non-ionic surfactants  
5 - 15 % anionic surfactants  
< 5 % cationic surfactants

## Safety equipment

Eye / Face protection:	suitable safety goggles acc. EN 166	In case of splash
Hand protection:	suitable gloves type EN 374	In case of possible or prolonged skin contact
Respiratory protection:	Combination filtering device DIN EN 14387	In case of exceeding exposure limit values, Type: A

## Application

Stripper can be used in immersion- and ultrasonic processes as well as in manual applications. The optimal cleaning temperature is 60 - 80 °C, but already effective at room temperature. Normally Aluminium will be not damaged. Nevertheless, it is advisable to test the Cleaner prior to the actual use on an unobtrusive spot.

## Technical data

Appearance :	liquid	Solidifying temperature :	< 0 °C
Colour :	colourless	Ignition temperature :	not relevant
Odour :	characteristic	Upper explosion limit :	not relevant
Boiling temperature :	ca. 100 °C	pH-value :	ca. 12,5
Flash point :	not relevant	VOC (CH) :	17.5 Wt %
Lower explosion limit :	not relevant		
Density (20 °C) :	ca. 1,03 g/cm <sup>3</sup>		
VOC (EG) :	7.5 Wt %		

## Storage

Keep container tightly closed. Keep/store only in original container. Protect against sub-zero temperatures. Optimized storage temperature is between 2 °C up to 35 °C. The product is storable in closed original packaging for at least 12 months. Starting date is the date of production.  
Storage class (acc. TRGS 510): 12

## Disposal advices

The waste codes are recommendations based on the schedule use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances.

Waste code acc. EWC/AVV for unused product		Waste code acc. EWC/AVV for packaging	
20 01 29*	detergents containing dangerous substances.	15 01 02	plastic packaging
07 06 99	wastes not otherwise specified.		

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

## Order information

<b>A00176</b>	1000 ml PET bottle with trigger – TU: 12 x 1000 ml ( 1 box)
<b>A01076</b>	10 l Jerry can
<b>A02076</b>	20 l Jerry can
<b>A20076</b>	200 l Drum
<b>A10076</b>	1000 l IBC