

PRODUCT NO. 5353-150360

DOTLUX WORKERrocket construction site spotlight 70W 5000K CRI>92 IP54 IK07



to the product page

- Easy to transport thanks to compact design and ergonomic carrying handle
- High stability thanks to integrated tripod guarantees safe working
- 3 m flexible H07RNF rubber cable for optimum use on the construction site or outdoors
- Integrated cable holder
- Additional socket IP 54 maximum 1800 Watt / 230 Volt /16A
- Glare-free all-round lighting with 360° beam angle
- Most natural color rendering CRI >92 for demanding users
- Splash-proof IP 54 housing

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	5353-050360
WEIGHT IN KG	4.22
LUMEN PER WATT	94
POWER CONSUMPTION IN WATTS	70
NET LUMINOUS FLUX IN LUMENS	6600

Dimensions

height: 1370mm
length: 665mm
width: 665mm

BEAM ANGLE	360
PROTECTION CLASS (IP)	IP54
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 30.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	5000
COLOR-RENDERING-INDEX	CRI > 92
INRUSH CURRENT IN A	0
IK PROTECTION	IK07
LUMEN PER WATT	94
PROTECTION CLASS	I
WARRANTY IN YEARS	2
ENABLED LICENSED PRODUCT	Yes
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
MOUNTING LOCATION	Indoor + covered outdoor
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	45000
ETIM GROUP IDENTIFICATION NUMBER	EC000346
IMPACT STRENGTH	IK07
CONNECTION TYPE	Cable
LIFETIME L70/B50 AT 25°C	45000
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany