




CERTIFICAZIONI INTERNAZIONALI
INTERNATIONAL ACCREDITATIONS
INTERNATIONALE ZULASSUNGEN



V

Update: 01/2023



ACCIAIO INOX AISI 316L
STAINLESS STEEL AISI 316L
EDELSTAHL AISI 316L



Germany



Switzerland



Norway




ACCIAIO AL CARBONIO
CARBON STEEL
C-STAHL




Sweden





RISE




Manicotto misto - filetto maschio

Adaptor with male thread

Übergangsmuffe A.G.

| Code | d - R | L | H | | | MOQ |
|-------------|----------------------------------|----|----|-----|----|-----|
| C81NBVI-LBP | 12-R ³ / ₈ | 38 | 20 | 43 | 20 | 120 |
| C81PBVI-LBP | 12-R ¹ / ₂ | 40 | 22 | 55 | 20 | 120 |
| C81NCVI-LBP | 15-R ³ / ₈ | 45 | 24 | 52 | 20 | 200 |
| C81PCVI-LBP | 15-R ¹ / ₂ | 46 | 25 | 60 | 20 | 200 |
| C81QCVI-LBP | 15-R ³ / ₈ | 48 | 27 | 72 | 20 | 100 |
| C81PDVI-LBP | 18-R ¹ / ₂ | 47 | 26 | 67 | 20 | 200 |
| C81QDVI-LBP | 18-R ³ / ₈ | 49 | 28 | 93 | 20 | 160 |
| C81PEVI-LBP | 22-R ¹ / ₂ | 53 | 30 | 111 | 20 | 160 |
| C81QEVI-LBP | 22-R ³ / ₈ | 56 | 33 | 124 | 20 | 200 |
| C81REVI-LBP | 22-R1 | 56 | 33 | 164 | 20 | 200 |
| C81QFVI-LBP | 28-R ³ / ₈ | 50 | 26 | 138 | 10 | 200 |
| C81RFVI-LBP | 28-R1 | 52 | 28 | 150 | 10 | 200 |
| C81SGVI-LBP | 35-R ¹ / ₄ | 58 | 31 | 212 | 10 | 200 |
| C81TGV-LBP | 35-R ¹ / ₂ | 58 | 31 | 307 | 10 | 100 |
| C81THVI-LBP | 42-R ¹ / ₂ | 65 | 33 | 295 | 6 | 84 |
| C81VJVI-LBP | 54-R2 | 75 | 38 | 435 | 4 | 80 |




Gomito misto - filetto femmina

Elbow adaptor 90° with female thread

Übergangswinkel 90° I.G.

| Code | d - Rp | L | L1 | Z | Z1 | | | MOQ |
|-------------|-----------------------------------|----|----|----|----|-----|----|-----|
| C30PCVI-LBP | 15-Rp ¹ / ₂ | 47 | 27 | 26 | 15 | 186 | 20 | 100 |
| C30PDVI-LBP | 18-Rp ¹ / ₂ | 50 | 26 | 29 | 14 | 186 | 10 | 80 |
| C30PEVI-LBP | 22-Rp ¹ / ₂ | 53 | 40 | 30 | 28 | 250 | 10 | 50 |
| C30QEVI-LBP | 22-Rp ³ / ₈ | 56 | 30 | 33 | 17 | 315 | 10 | 50 |
| C30PFVI-LBP | 28-Rp ¹ / ₂ | 59 | 44 | 35 | 32 | 491 | 10 | 40 |



Gomito misto - filetto maschio

Elbow adaptor 90° with male thread

Übergangswinkel 90° A.G.

| Code | d - R | L | H | Z | | | MOQ |
|-------------|----------------------------------|----|----|----|-----|----|-----|
| C31NBVI-LBP | 12-R ³ / ₈ | 39 | 23 | 21 | 88 | 20 | 120 |
| C31NCVI-LBP | 15-R ³ / ₈ | 44 | 23 | 23 | 94 | 20 | 120 |
| C31PCVI-LBP | 15-R ¹ / ₂ | 44 | 27 | 23 | 108 | 20 | 120 |
| C31PDVI-LBP | 18-R ¹ / ₂ | 48 | 30 | 27 | 149 | 20 | 80 |
| C31QDVI-LBP | 18-R ³ / ₈ | 50 | 31 | 29 | 169 | 10 | 60 |
| C31QEVI-LBP | 22-R ³ / ₈ | 54 | 33 | 31 | 213 | 10 | 60 |